

A Donaldson Company

A WORLD LEADER IN FUME EXTRACTION TECHNOLOGY



**LASER** 

Last Updated on 07.03.2019





The AD 4000 iQ delivers superior and measurable performance, ensuring airflow and filtration is maintained even when particulates start to build up from the triple DeepPleat DUO and combined filter setup.

This makes it suitable for the most demanding and complex installations, so you can rely on extended filter life, together with effective removal of fumes and particulates.

It's user friendly too, with a design that makes easy work of filter changes and the easy to read and access controls display panel is conveniently located on top of the unit.

The AD 4000 iQ design permits greater flexibility. Different exhaust configurations allow recirculation via the rear panel or externally vented hose connection systems.

More information about the Intelligent (iQ) Operating System.

### **Technology**



Intelligent (iQ)
Operating System



DeepPleat DUO



**HEPA** filter



Automatic flow control technology



Reverse flow air technology



Advanced carbon filter technology



Patented technology



ProTECT service plan



SureCHECK quality standard

Key features of the AD 4000 iQ

**iQ Operating system** Standard **3 x DeepPleat DUO pre filters** Standard

Contact BOFA at https://bofainternational.com/en/contact/

https://bofainternational.com/en/portal/datasheets/ad-4000-iq/















Reverse flow air filter technology

Standard

Blowers with high airflow and vacuum levels

Standard

Real time airflow reading

Standard

Remote diagnostics via USB

Standard

Long life filters with low replacement cost

Standard

Remote stop / start interface

Optional

VOC gas sensor (Volatile Organic Compound)

Optional

On-board compressor

Optional

Combined HEPA/Gas filter incorporating ACF technology

Standard

High contrast display

Standard

Filter status warnings

Standard

Independent filter condition monitoring

Standard

'Run safe' operation (filters must be installed correctly for the

unit to operate)

Standard

Filter change / System fail signal

Optional

Interfacing with host laser

Optional

## **Technical specification**

1 iQ Display

2 Standby button

3 Signal / interface cable

4 Power cable inlet

**5** Adjustable locking castors

6 Door hinges

7 Exhaust outlet

8 Hose inlet connection -


200mm

9 Removable front panels

10 Motor cooling inlet

11 Motor cooling outlet

12 On / off switch



# Airflow through filters

Chemical filter



HEPA filter



Pre filter




Clean air



Contaminated air



Particulate



Technical data				
	EU	US		
Dimensions (H x W x D) (height varies due to adjustable castors)	1300 x 1955 x 1100mm	51.18 x 76.97 x 43.31"		
Cabinet construction	Powder coated mild steel	Powder coated mild steel		
Airflow/Pressure	2900m³/hr / 44mbar	1705cfm / 44mbar		
Electrical data	(EU) 415V / 3Ph / 50Hz / 6.6kw / 16A / L1, L2, L3 17A - N 1A	(EU) 415V / 3Ph / 50Hz / 6.6kw / 16A / L1, L2, L3 17A - N 1A		
Noise level	< 82dBA (at typical operating speed)	< 82dBA (at typical operating speed)		
Weight	580kgs	1276lbs		
Approvals	CE	CE		

3 x Combined HEPA/Gas filter specifications			
Surface media area	7.5m² approx x 3 (22.5m²) 80.7 ft² approx x 3 (242.1 ft²)		
HEPA filter media	Glass fibre		
HEPA media construction	Maxi pleat construction with webbing spacers		
Filter housing	Zintec mild steel		
Treated activated carbon	34kgs (102kgs) 74.8 lbs (224.4 lbs)		
Filter efficiency	99.997% @ 0.3 microns		

3 x DeepPleat DUO pre filter specifications			
Surface media area	30m² approx x 3 (90m²) 322.8 ft² approx x 3 (968.4 ft²)		
Filter media	Glass fibre		
Filter media construction	Maxi pleat construction with webbing spacers		
Filter housing	Zintec mild steel		
Filter efficiency	95% @ 0.9 microns		
Inlet size	125mm (0.41ft)		
Dropout chamber size	58 litres x 3 (174 litres)		

#### 3 x DeepPleat DUO pre filter specifications

Filter media pleat size

200mm x 3 (600mm) 0.65ft x 3 (1.95ft)

Unit part numbers				
Model	24V Stop / Start	Filter change / System failure signal	VOC monitoring	Part no.
AD 4000 iQ powder coated	YES	YES	NO	296295812128-1743
AD 4000 iQ powder coated	YES	YES	YES	304395812128-1743

Replacement filter part numbers		
Model	Triple pack DeepPleat DUO pre filters	Triple pack combined HEPA/Gas filters
AD 4000 iQ	A1030407	A1030406

## Other languages

AD 4000 iQ French

Datasheet correct at time of publishing.

Where applicable, the carbon used in BOFA units is capable of removing a wide range of VOC's, however it is the responsibility of the user to ensure the carbon is suitable for their application. For specific applications, please contact us for details.

Think before you print! Please consider the environment before printing this document.

