

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Sprayflon

Print date: 10.01.2017

Product code: 113

Page 1 of 8

SECTION 1: Identification of the substance/mixture and of the company/undertaking**1.1. Product identifier**

Sprayflon

1.2. Relevant identified uses of the substance or mixture and uses advised against**Use of the substance/mixture**

Lubricants, greases, release products

Uses advised against

Reserved for industrial and professional use.

1.3. Details of the supplier of the safety data sheet

Company name:	ITW LLC & Co. KG	
Street:	Mühlackerstrasse 149	
Place:	D-75417 Mühlacker	
Telephone:	++49(0)7041-96340	Telefax: ++49(0)7041-963429
e-mail:	info@itwcp.de	
Internet:	www.itwcp.de	
Responsible Department:	Produktsicherheit	

1.4. Emergency telephone number:++49(0)7041-96340
Mo. - Do. 8.00 - 16.30 Fr. 8.00 - 14.00**SECTION 2: Hazards identification****2.1. Classification of the substance or mixture****Regulation (EC) No. 1272/2008**

Hazard categories:

Aerosol: Aerosol 1

Serious eye damage/eye irritation: Eye Irrit. 2

Specific target organ toxicity - single exposure: STOT SE 3

Hazardous to the aquatic environment: Aquatic Chronic 2

Hazard Statements:

Extremely flammable aerosol.

Pressurised container: May burst if heated.

Causes serious eye irritation.

May cause drowsiness or dizziness.

Toxic to aquatic life with long lasting effects.

2.2. Label elements**Regulation (EC) No. 1272/2008****Hazard components for labelling**

Acetone, Isopropanol, Hydrocarbons

Signal word: Danger**Pictograms:****Hazard statements**

H222	Extremely flammable aerosol.
H229	Pressurised container: May burst if heated.
H319	Causes serious eye irritation.
H336	May cause drowsiness or dizziness.
H411	Toxic to aquatic life with long lasting effects.

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Sprayflon

Print date: 10.01.2017

Product code: 113

Page 2 of 8

Precautionary statements

P273	Avoid release to the environment.
P410+P412	Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.
P251	Do not pierce or burn, even after use.
P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P271	Use only outdoors or in a well-ventilated area.
P305+P351+P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Hazardous components

CAS No	Chemical name	Quantity
	EC No	
	Index No	
	REACH No	
	Classification according to Regulation (EC) No. 1272/2008 [CLP]	
64742-49-0	Naphtha (petroleum), hydrotreated light; Low boiling point hydrogen treated naphtha, <5% n-hexane	40-60%
	931-254-9	
	Flam. Liq. 2, STOT SE 3, Asp. Tox. 1, Aquatic Chronic 2; H225 H336 H304 H411	
67-64-1	acetone; propan-2-one; propanone	25-50%
	200-662-2	
	606-001-00-8	
	Flam. Liq. 2, Eye Irrit. 2, STOT SE 3; H225 H319 H336 EUH066	
124-38-9	Carbondioxide	<10%
	204-696-9	
	Compressed gas; H280	
67-63-0	propan-2-ol; isopropyl alcohol; isopropanol	1-10%
	200-661-7	
	603-117-00-0	
	Flam. Liq. 2, Eye Irrit. 2, STOT SE 3; H225 H319 H336	

Full text of H and EUH statements: see section 16.

SECTION 4: First aid measures

4.1. Description of first aid measures

After inhalation

Provide fresh air. In case of accident or unwellness, seek medical advice immediately (show directions for use or safety data sheet if possible).

After contact with skin

After contact with skin, wash immediately with: Water. Change contaminated clothing.

After contact with eyes

If product gets into the eye, keep eyelid open and rinse immediately with large quantities of water, for at least 5 minutes. Subsequently consult an ophthalmologist.

After ingestion

If swallowed, immediately drink: Water.

4.2. Most important symptoms and effects, both acute and delayed

No data available

4.3. Indication of any immediate medical attention and special treatment needed

No data available

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Sprayflon

Print date: 10.01.2017

Product code: 113

Page 3 of 8

SECTION 5: Firefighting measures**5.1. Extinguishing media****Suitable extinguishing media**Carbon dioxide (CO₂). Foam. Extinguishing powder.**Unsuitable extinguishing media**

Water. Water with tenside additive.

5.2. Special hazards arising from the substance or mixture

Combustible. Vapours may form explosive mixtures with air. Heating causes rise in pressure with risk of bursting.

5.3. Advice for firefighters

Wear a self-contained breathing apparatus and chemical protective clothing.

Additional information

Use water spray jet to protect personnel and to cool endangered containers. Suppress gases/vapours/mists with water spray jet. Contaminated fire-fighting water must be collected separately. Do not allow to enter into surface water or drains.

SECTION 6: Accidental release measures**6.1. Personal precautions, protective equipment and emergency procedures**

Remove all sources of ignition. Provide adequate ventilation. Wear a self-contained breathing apparatus and chemical protective clothing.

6.2. Environmental precautions

Do not allow to enter into surface water or drains. Explosion hazard.

6.3. Methods and material for containment and cleaning up

Ventilate affected area.

SECTION 7: Handling and storage**7.1. Precautions for safe handling****Advice on safe handling**

If handled uncovered, arrangements with local exhaust ventilation have to be used. Do not breathe gas/fumes/vapour/spray.

Advice on protection against fire and explosion

Keep away from sources of ignition. - No smoking.

7.2. Conditions for safe storage, including any incompatibilities**Requirements for storage rooms and vessels**

Keep container tightly closed. Keep in a cool, well-ventilated place. Keep away from sources of ignition. - No smoking.

Advice on storage compatibility

Do not store together with: Material, rich in oxygen, oxidizing.

SECTION 8: Exposure controls/personal protection**8.1. Control parameters**

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Sprayflon

Print date: 10.01.2017

Product code: 113

Page 4 of 8

Exposure limits (EH40)

CAS No	Substance	ppm	mg/m ³	fibres/ml	Category	Origin
67-64-1	Acetone	500	1210		TWA (8 h)	WEL
		1500	3620		STEL (15 min)	WEL
124-38-9	Carbon dioxide	5000	9150		TWA (8 h)	WEL
		15000	27400		STEL (15 min)	WEL
67-63-0	Propan-2-ol	400	999		TWA (8 h)	WEL
		500	1250		STEL (15 min)	WEL

8.2. Exposure controls



Appropriate engineering controls

If handled uncovered, arrangements with local exhaust ventilation have to be used. Do not breathe gas/fumes/vapour/spray.

Protective and hygiene measures

Remove contaminated, saturated clothing immediately. Protect skin by using skin protective cream. After work, wash hands and face. When using do not eat or drink.

Eye/face protection

Tightly sealed safety glasses.

Hand protection

DIN EN 374 Tested protective gloves are to be worn: Butyl rubber. For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves.

Skin protection

Protective clothing:

Respiratory protection

In case of inadequate ventilation wear respiratory protection.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state:	Aerosol
Colour:	colourless
Odour:	characteristic

Test method

Changes in the physical state

Initial boiling point and boiling range:	56 °C
Flash point:	<0 °C
Lower explosion limits:	1,2 vol. %
Upper explosion limits:	14,3 vol. %
Density:	0,726 g/cm ³

SECTION 10: Stability and reactivity

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Sprayflon

Print date: 10.01.2017

Product code: 113

Page 5 of 8

10.1. Reactivity

No data available

10.2. Chemical stability

No data available

10.3. Possibility of hazardous reactions

No data available

10.4. Conditions to avoid

Keep away from heat. Ignition hazard.

10.5. Incompatible materials

No data available

10.6. Hazardous decomposition products

No data available

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity

CAS No	Chemical name				
	Exposure route	Dose		Species	Source
67-64-1	acetone; propan-2-one; propanone				
	oral	LD50	5800 mg/kg	Rat	RTECS
	dermal	LD50	20000 mg/kg	Rabbit	IUCLID
	inhalative (4 h) vapour	LC50	76 mg/l	Rat	

Irritation and corrosivity

Irritating to eyes. Vapours may cause drowsiness and dizziness. After skin contact: Irritant.

Additional information on tests

The classification was carried out according to the calculation method of the Preparations Directive (1999/45/EC).

SECTION 12: Ecological information

12.1. Toxicity

Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

CAS No	Chemical name				
	Aquatic toxicity	Dose	[h] [d]	Species	Source
67-64-1	acetone; propan-2-one; propanone				
	Acute fish toxicity	LC50	5540 mg/l	96 h	Onchorhynchus mykiss
	Acute crustacea toxicity	EC50	6100 mg/l	48 h	Daphnia magna

12.3. Bioaccumulative potential

Partition coefficient n-octanol/water

CAS No	Chemical name	Log Pow
67-64-1	acetone; propan-2-one; propanone	-0,24

Further information

Do not allow to enter into surface water or drains. The classification was carried out according to the calculation method of the Preparations Directive (1999/45/EC).

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Sprayflon

Print date: 10.01.2017

Product code: 113

Page 6 of 8

SECTION 13: Disposal considerations**13.1. Waste treatment methods****Advice on disposal**

Do not allow to enter into surface water or drains. Dispose of waste according to applicable legislation.

Waste disposal number of waste from residues/unused products

160504 WASTES NOT OTHERWISE SPECIFIED IN THE LIST; gases in pressure containers and discarded chemicals; gases in pressure containers (including halons) containing hazardous substances
Classified as hazardous waste.

Waste disposal number of contaminated packaging

150104 WASTE PACKAGING; ABSORBENTS, WIPING CLOTHS, FILTER MATERIALS AND PROTECTIVE CLOTHING NOT OTHERWISE SPECIFIED; packaging (including separately collected municipal packaging waste); metallic packaging

Contaminated packaging

Non-contaminated packages may be recycled. Handle contaminated packages in the same way as the substance itself.

SECTION 14: Transport information**Land transport (ADR/RID)**

14.1. UN number: UN1950
14.2. UN proper shipping name: AEROSOLS
14.3. Transport hazard class(es): 2
Hazard label: 2.1



Classification code: 5F
Special Provisions: 190 327 625
Limited quantity: 1 L
Transport category: 2
Tunnel restriction code: D

Other applicable information (land transport)

E0

Inland waterways transport (ADN)

14.1. UN number: UN1950
14.2. UN proper shipping name: AEROSOLS
14.3. Transport hazard class(es): 2
Hazard label: 2.1



Classification code: 5F
Special Provisions: 190 327 344 625
Limited quantity: 1 L

Other applicable information (inland waterways transport)

E0

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Sprayflon

Print date: 10.01.2017

Product code: 113

Page 7 of 8

Marine transport (IMDG)

14.1. UN number: UN1950
14.2. UN proper shipping name: AEROSOLS
14.3. Transport hazard class(es): 2
14.4. Packing group: -
Hazard label: 2, see SP63

Special Provisions: 63, 190, 277, 327, 344, 959
Limited quantity: See SP277
EmS: F-D, S-U

Other applicable information (marine transport)
E0

Air transport (ICAO)

14.1. UN number: UN1950
14.2. UN proper shipping name: AEROSOLS, flammable
14.3. Transport hazard class(es): 2.1
Hazard label: 2.1



Special Provisions: A145 A167
Limited quantity Passenger: 30 kg G
IATA-packing instructions - Passenger: 203
IATA-max. quantity - Passenger: 75 kg
IATA-packing instructions - Cargo: 203
IATA-max. quantity - Cargo: 150 kg

Other applicable information (air transport)
E0
: Y203

14.5. Environmental hazards

ENVIRONMENTALLY HAZARDOUS: yes



Danger releasing substance: Hydrocarbons

SECTION 15: Regulatory information**15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture****EU regulatory information**

2004/42/EC (VOC): 86,94 %

National regulatory information

Water contaminating class (D): 2 - water contaminating

SECTION 16: Other information

**Safety Data Sheet**

according to Regulation (EC) No 1907/2006

Sprayflon

Print date: 10.01.2017

Product code: 113

Page 8 of 8

Relevant H and EUH statements (number and full text)

H222	Extremely flammable aerosol.
H225	Highly flammable liquid and vapour.
H229	Pressurised container: May burst if heated.
H280	Contains gas under pressure; may explode if heated.
H304	May be fatal if swallowed and enters airways.
H319	Causes serious eye irritation.
H336	May cause drowsiness or dizziness.
H411	Toxic to aquatic life with long lasting effects.
EUH066	Repeated exposure may cause skin dryness or cracking.

(The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)