

according to Regulation (EC) No 1907/2006

Degeaser

Product code: 106 Print date: 10.01.2017 Page 1 of 8

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Degeaser

1.2. Relevant identified uses of the substance or mixture and uses advised against

Uses advised against

Reserved for industrial and professional use.

1.3. Details of the supplier of the safety data sheet

ITW LLC & Co. KG Company name: Street: Mühlackerstrasse 149 Place: D-75417 Mühlacker

Telephone: ++49(0)7041-96340 Telefax: ++49(0)7041-963429

e-mail: info@itwcp.de www.itwcp.de Internet: Responsible Department: Produktsicherheit

1.4. Emergency telephone ++49(0)7041-96340

Mo. - Do. 8.00 - 16.30 Fr. 8.00 - 14.00 number:

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Regulation (EC) No. 1272/2008

Hazard categories: Aerosol: Aerosol 1

Skin corrosion/irritation: Skin Irrit. 2

Serious eye damage/eye irritation: Eye Irrit. 2

Specific target organ toxicity - single exposure: STOT SE 3 Hazardous to the aquatic environment: Aquatic Chronic 3

Hazard Statements:

Extremely flammable aerosol.

Pressurised container: May burst if heated.

Causes serious eye irritation. May cause drowsiness or dizziness.

Harmful to aquatic life with long lasting effects.

2.2. Label elements

Regulation (EC) No. 1272/2008

Hazard components for labelling

Propan-2-ol, 1-Methoxy-2-propanol, Monopropylenglycolmethylether, Hydrocarbons

Signal word: Danger

Pictograms:





Hazard statements

H222 Extremely flammable aerosol.

H229 Pressurised container: May burst if heated.

H319 Causes serious eye irritation. H336 May cause drowsiness or dizziness.

H412 Harmful to aquatic life with long lasting effects.



according to Regulation (EC) No 1907/2006

Degeaser

Print date: 10.01.2017 Product code: 106 Page 2 of 8

Precautionary statements

P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.

P273 Avoid release to the environment.
P251 Do not pierce or burn, even after use.

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No

smoking.

P271 Use only outdoors or in a well-ventilated area.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if

present and easy to do. Continue rinsing.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Hazardous components

CAS No	Chemical name					
	EC No	Index No	REACH No			
	Classification according to Regulati	on (EC) No. 1272/2008 [CLP]	•			
67-63-0	propan-2-ol; isopropyl alcohol; isopropanol					
	200-661-7	603-117-00-0				
	Flam. Liq. 2, Eye Irrit. 2, STOT SE 3; H225 H319 H336					
107-98-2	1-Methoxy-2-propanol					
	203-539-1		01-2119457435-35			
	Flam. Liq. 3, STOT SE 3; H226 H336					
64742-95-6	Solvent naphta light					
	265-199-0		01-2119463881-32			
	Flam. Liq. 3, STOT SE 3, Asp. Tox. 1, Aquatic Chronic 2; H226 H335 H304 H411					
124-38-9	24-38-9 Carbondioxide					
	204-696-9					
	Compressed gas; H280					

Full text of H and EUH statements: see section 16.

SECTION 4: First aid measures

4.1. Description of first aid measures

After inhalation

Provide fresh air. In case of accident or unwellness, seek medical advice immediately (show directions for use or safety data sheet if possible).

After contact with skin

After contact with skin, wash immediately with: Water. Change contaminated clothing.

After contact with eyes

If product gets into the eye, keep eyelid open and rinse immediately with large quantities of water, for at least 5 minutes. Subsequently consult an ophthalmologist.

After ingestion

If swallowed, immediately drink: Water.

4.2. Most important symptoms and effects, both acute and delayed

No data available

4.3. Indication of any immediate medical attention and special treatment needed

No data available



ITW LLC & Co. KG

according to Regulation (EC) No 1907/2006

Degeaser

Print date: 10.01.2017 Product code: 106 Page 3 of 8

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media

Carbon dioxide (CO2). Foam. Extinguishing powder.

Unsuitable extinguishing media

Water with tenside additive. Water.

5.2. Special hazards arising from the substance or mixture

Combustible. Vapours may form explosive mixtures with air. Heating causes rise in pressure with risk of bursting.

5.3. Advice for firefighters

Wear a self-contained breathing apparatus and chemical protective clothing.

Additional information

Suppress gases/vapours/mists with water spray jet. Contaminated fire-fighting water must be collected separately. Do not allow to enter into surface water or drains.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Remove all sources of ignition. Provide adequate ventilation. Wear a self-contained breathing apparatus and chemical protective clothing.

6.2. Environmental precautions

Do not allow to enter into surface water or drains. Explosion hazard.

6.3. Methods and material for containment and cleaning up

Ventilate affected area.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Advice on safe handling

If handled uncovered, arrangements with local exhaust ventilation have to be used. Do not breathe gas/fumes/vapour/spray.

Advice on protection against fire and explosion

Keep away from sources of ignition. - No smoking.

7.2. Conditions for safe storage, including any incompatibilities

Requirements for storage rooms and vessels

Keep container tightly closed. Keep in a cool, well-ventilated place. Keep away from sources of ignition. - No smoking.

Advice on storage compatibility

Do not store together with: Material, rich in oxygen, oxidizing

SECTION 8: Exposure controls/personal protection

8.1. Control parameters



according to Regulation (EC) No 1907/2006

Degeaser

Print date: 10.01.2017 Product code: 106 Page 4 of 8

Exposure limits (EH40)

CAS No	Substance	ppm	mg/m³	fibres/ml	Category	Origin
107-98-2	1-Methoxypropan-2-ol	100	375		TWA (8 h)	WEL
		150	560		STEL (15 min)	WEL
124-38-9	Carbon dioxide	5000	9150		TWA (8 h)	WEL
		15000	27400		STEL (15 min)	WEL
67-63-0	Propan-2-ol	400	999		TWA (8 h)	WEL
		500	1250		STEL (15 min)	WEL

8.2. Exposure controls





Appropriate engineering controls

If handled uncovered, arrangements with local exhaust ventilation have to be used. Do not breathe gas/fumes/vapour/spray.

Protective and hygiene measures

Remove contaminated, saturated clothing immediately. Protect skin by using skin protective cream. After work, wash hands and face. When using do not eat or drink.

Eye/face protection

Tightly sealed safety glasses.

Hand protection

DIN EN 374 Tested protective gloves are to be worn: Butyl rubber. For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves.

Skin protection

Protective clothing:

Respiratory protection

In case of inadequate ventilation wear respiratory protection.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state: Aerosol
Colour: colourless
Odour: characteristic

Test method

Changes in the physical state

Initial boiling point and boiling range:	82,4 °C
Flash point:	<0 °C
Lower explosion limits:	1,8 vol. %
Upper explosion limits:	13,1 vol. %
Ignition temperature:	270 °C
Vapour pressure: (at 20 °C)	13,3 hPa



according to Regulation (EC) No 1907/2006

Degeaser

Print date: 10.01.2017 Product code: 106 Page 5 of 8

Vapour pressure:

60 hPa

(at 50 °C)

Density (at 0,82 °C):

0,82 g/cm³

Solvent content:

34,40 %

SECTION 10: Stability and reactivity

10.1. Reactivity

No data available

10.2. Chemical stability

No data available

10.3. Possibility of hazardous reactions

No data available

10.4. Conditions to avoid

Keep away from heat. Ignition hazard.

10.5. Incompatible materials

No data available

10.6. Hazardous decomposition products

No data available

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity

CAS No	Chemical name						
	Exposure route	Dose		Species	Source		
64742-95-6	Solvent naphta light						
	oral	LD50	3592 mg/kg	Rat			
	dermal	LD50	3160 mg/kg	Rabbit			
	inhalative (4 h) vapour	LC50	6,193 mg/l	Rat			

Irritation and corrosivity

Irritating to eyes. Following inhalation: Lung irritation. Coughing. shortage of breath. After skin contact: Irritant.

Additional information on tests

The classification was carried out according to the calculation method of the Preparations Directive (1999/45/EC).

SECTION 12: Ecological information

12.1. Toxicity

Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

CAS No	Chemical name							
	Aquatic toxicity	Dose		[h] [d]	Species	Source		
64742-95-6	Solvent naphta light							
	Acute fish toxicity	LC50	9,22 mg/l	96 h	Fisch			
	Acute algae toxicity	ErC50	2,9 mg/l	72 h	Alge			
	Acute crustacea toxicity	EC50	6,14 mg/l		Daphnia magna (Big water flea)			



according to Regulation (EC) No 1907/2006

Degeaser

Print date: 10.01.2017 Product code: 106 Page 6 of 8

Further information

Do not allow to enter into surface water or drains. The classification was carried out according to the calculation method of the Preparations Directive (1999/45/EC).

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Advice on disposal

Do not allow to enter into surface water or drains. Dispose of waste according to applicable legislation.

Waste disposal number of waste from residues/unused products

160504 WASTES NOT OTHERWISE SPECIFIED IN THE LIST; gases in pressure containers and

discarded chemicals; gases in pressure containers (including halons) containing hazardous

substances

Classified as hazardous waste.

Waste disposal number of contaminated packaging

150104 WASTE PACKAGING; ABSORBENTS, WIPING CLOTHS, FILTER MATERIALS AND

PROTECTIVE CLOTHING NOT OTHERWISE SPECIFIED; packaging (including separately

collected municipal packaging waste); metallic packaging

Contaminated packaging

Non-contaminated packages may be recycled. Handle contaminated packages in the same way as the substance itself.

SECTION 14: Transport information

Land transport (ADR/RID)

14.1. UN number:UN195014.2. UN proper shipping name:AEROSOLS

14.3. Transport hazard class(es): 2
Hazard label: 2.1



Classification code: 5F

Special Provisions: 190 327 625

Limited quantity: 1 L
Transport category: 2
Tunnel restriction code: D

Other applicable information (land transport)

E

Inland waterways transport (ADN)

14.1. UN number:UN195014.2. UN proper shipping name:AEROSOLS


14.3. Transport hazard class(es): 2
Hazard label: 2.1



Classification code: 5F

Special Provisions: 190 327 344 625

Limited quantity: 1 L





according to Regulation (EC) No 1907/2006

Degeaser

Print date: 10.01.2017 Product code: 106 Page 7 of 8

Other applicable information (inland waterways transport)

E0

Marine transport (IMDG)

14.1. UN number: UN1950
14.2. UN proper shipping name: AEROSOLS

14.3. Transport hazard class(es): 2
14.4. Packing group: -

Hazard label: 2. see SP63

Special Provisions: 63, 190, 277, 327, 344, 959

Limited quantity: See SP277 EmS: F-D, S-U

Other applicable information (marine transport)

Εſ

Air transport (ICAO)

14.1. UN number: UN1950

14.2. UN proper shipping name: AEROSOLS, flammable

14.3. Transport hazard class(es):2.1Hazard label:2.1



Special Provisions: A145 A167 Limited quantity Passenger: 30 kg G

IATA-packing instructions - Passenger:203IATA-max. quantity - Passenger:75 kgIATA-packing instructions - Cargo:203IATA-max. quantity - Cargo:150 kg

Other applicable information (air transport)

E0 : Y203

14.5. Environmental hazards

ENVIRONMENTALLY HAZARDOUS: no

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

EU regulatory information

2004/42/EC (VOC): 34,4 %

National regulatory information

Water contaminating class (D): 2 - water contaminating

SECTION 16: Other information

Relevant H and EUH statements (number and full text)

H222 Extremely flammable aerosol.



according to Regulation (EC) No 1907/2006

Degeaser							
Print date: 10.01.2017	Product code: 106	Page 8 of 8					
H225	Highly flammable liquid and vapour.						
H226	Flammable liquid and vapour.						
H229	Pressurised container: May burst if heated.						
H280	Contains gas under pressure; may explode if heated.						
H304	May be fatal if swallowed and enters airways.						
H319	Causes serious eye irritation.						
H335	May cause respiratory irritation.						
H336	May cause drowsiness or dizziness.						
H411	Toxic to aquatic life with long lasting effects.						
H412	Harmful to aquatic life with long lasting effects.						

(The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)