

**Safety Data Sheet**

according to Regulation (EC) No 1907/2006

**Kabelglide**

Print date: 06.02.2017

Product code: 151

Page 1 of 7

**SECTION 1: Identification of the substance/mixture and of the company/undertaking****1.1. Product identifier**

Kabelglide

**1.2. Relevant identified uses of the substance or mixture and uses advised against****Uses advised against**

Reserved for industrial and professional use.

**1.3. Details of the supplier of the safety data sheet**

Company name:	ITW LLC & Co. KG	
Street:	Mühlackerstrasse 149	
Place:	D-75417 Mühlacker	
Telephone:	++49(0)7041-96340	Telefax: ++49(0)7041-963429
e-mail:	info@itwcp.de	
Internet:	www.itwcp.de	
Responsible Department:	Produktsicherheit	

**1.4. Emergency telephone**

number: ++49(0)7041-96340  
Mo. - Do. 8.00 - 16.30 Fr. 8.00 - 14.00

**SECTION 2: Hazards identification****2.1. Classification of the substance or mixture****Regulation (EC) No. 1272/2008**

Hazard categories:

Aerosol: Aerosol 1

Specific target organ toxicity - single exposure: STOT SE 3

Hazardous to the aquatic environment: Aquatic Chronic 2

Hazard Statements:

Extremely flammable aerosol.

Pressurised container: May burst if heated.

May cause drowsiness or dizziness.

Toxic to aquatic life with long lasting effects.

**2.2. Label elements****Regulation (EC) No. 1272/2008****Hazard components for labelling**

Hydrocarbons, C6, isoalkanes, &lt;5% n-hexane, &lt;0.1% of Benzene

Signal word: Danger

Pictograms:

**Hazard statements**

H222	Extremely flammable aerosol.
H229	Pressurised container: May burst if heated.
H336	May cause drowsiness or dizziness.
H411	Toxic to aquatic life with long lasting effects.

**Precautionary statements**

P410+P412	Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.
P273	Avoid release to the environment.
P271	Use only outdoors or in a well-ventilated area.
P251	Do not pierce or burn, even after use.

**Safety Data Sheet**

according to Regulation (EC) No 1907/2006

**Kabelglide**

Print date: 06.02.2017

Product code: 151

Page 2 of 7

P210

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

**SECTION 3: Composition/information on ingredients****3.2. Mixtures****Hazardous components**

CAS No	Chemical name			Quantity
	EC No	Index No	REACH No	
	Classification according to Regulation (EC) No. 1272/2008 [CLP]			
64742-49-0	Naphtha (petroleum), hydrotreated light; Low boiling point hydrogen treated naphtha, <5% n-hexane			25-50%
	931-254-9			
	Flam. Liq. 2, STOT SE 3, Asp. Tox. 1, Aquatic Chronic 2; H225 H336 H304 H411			
74-98-6	propane			15-25 %
	200-827-9	601-003-00-5		
	Flam. Gas 1; H220			
106-97-8	butane			15-25 %
	203-448-7	601-004-00-0		
	Flam. Gas 1; H220			

Full text of H and EUH statements: see section 16.

**SECTION 4: First aid measures****4.1. Description of first aid measures****After inhalation**

Provide fresh air. In case of accident or unwellness, seek medical advice immediately (show directions for use or safety data sheet if possible).

**After contact with skin**

After contact with skin, wash immediately with: Water. Change contaminated clothing.

**After contact with eyes**

Rinse immediately carefully and thoroughly with eye-bath or water.

**After ingestion**

If swallowed, immediately drink: Water.

**4.2. Most important symptoms and effects, both acute and delayed**

No data available

**4.3. Indication of any immediate medical attention and special treatment needed**

No data available

**SECTION 5: Firefighting measures****5.1. Extinguishing media****Suitable extinguishing media**Carbon dioxide (CO<sub>2</sub>). Foam. Extinguishing powder.**Unsuitable extinguishing media**

Water with tenside additive. Water.

**5.2. Special hazards arising from the substance or mixture**

Combustible. Vapours may form explosive mixtures with air. Heating causes rise in pressure with risk of bursting.

## Safety Data Sheet

according to Regulation (EC) No 1907/2006

### Kabelglide

Print date: 06.02.2017

Product code: 151

Page 3 of 7

#### 5.3. Advice for firefighters

Wear a self-contained breathing apparatus and chemical protective clothing.

#### Additional information

Use water spray jet to protect personnel and to cool endangered containers. Suppress gases/vapours/mists with water spray jet. Contaminated fire-fighting water must be collected separately. Do not allow to enter into surface water or drains.

### SECTION 6: Accidental release measures

#### 6.1. Personal precautions, protective equipment and emergency procedures

Remove all sources of ignition. Provide adequate ventilation. Wear a self-contained breathing apparatus and chemical protective clothing.

#### 6.2. Environmental precautions

Do not allow to enter into surface water or drains. Explosion hazard.

#### 6.3. Methods and material for containment and cleaning up

Ventilate affected area.

### SECTION 7: Handling and storage

#### 7.1. Precautions for safe handling

##### Advice on safe handling

If handled uncovered, arrangements with local exhaust ventilation have to be used. Do not breathe gas/fumes/vapour/spray.

##### Advice on protection against fire and explosion

Keep away from sources of ignition. - No smoking.

#### 7.2. Conditions for safe storage, including any incompatibilities

##### Requirements for storage rooms and vessels

Keep container tightly closed. Keep in a cool, well-ventilated place. Keep away from sources of ignition. - No smoking.

##### Advice on storage compatibility

Do not store together with: Material, rich in oxygen, oxidizing.

### SECTION 8: Exposure controls/personal protection

#### 8.1. Control parameters

##### Exposure limits (EH40)

CAS No	Substance	ppm	mg/m <sup>3</sup>	fibres/ml	Category	Origin
106-97-8	Butane	600	1450		TWA (8 h)	WEL
		750	1810		STEL (15 min)	WEL

#### 8.2. Exposure controls



##### Appropriate engineering controls

If handled uncovered, arrangements with local exhaust ventilation have to be used. Do not breathe gas/fumes/vapour/spray.

##### Protective and hygiene measures

Remove contaminated, saturated clothing immediately. Protect skin by using skin protective cream. After work,

**Safety Data Sheet**

according to Regulation (EC) No 1907/2006

**Kabelglide**

Print date: 06.02.2017

Product code: 151

Page 4 of 7

wash hands and face. When using do not eat or drink.

**Eye/face protection**

Tightly sealed safety glasses.

**Hand protection**

DIN EN 374 Tested protective gloves are to be worn: Butyl rubber. For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves.

**Skin protection**

Protective clothing:

**Respiratory protection**

In case of inadequate ventilation wear respiratory protection.

**SECTION 9: Physical and chemical properties****9.1. Information on basic physical and chemical properties**

Physical state:	Aerosol
Colour:	
Odour:	characteristic

**Test method****Changes in the physical state**

Initial boiling point and boiling range:	-0,5 °C
Flash point:	< 0 °C
Lower explosion limits:	1,2 vol. %
Upper explosion limits:	9,4 vol. %
Ignition temperature:	298 °C
Vapour pressure: (at 20 °C)	2100 hPa
Vapour pressure: (at 50 °C)	4900 hPa
Density (at 20 °C):	0,72 g/cm <sup>3</sup>

**SECTION 10: Stability and reactivity****10.1. Reactivity**

No data available

**10.2. Chemical stability**

No data available

**10.3. Possibility of hazardous reactions**

No data available

**10.4. Conditions to avoid**

Keep away from heat. Ignition hazard.

**10.5. Incompatible materials**

No data available

**10.6. Hazardous decomposition products**

No data available

**SECTION 11: Toxicological information****11.1. Information on toxicological effects**

**Safety Data Sheet**

according to Regulation (EC) No 1907/2006

**Kabelglide**

Print date: 06.02.2017

Product code: 151

Page 5 of 7

**Acute toxicity**

CAS No	Chemical name	Exposure route	Dose	Species	Source
106-97-8	butane	inhalative (4 h) gas	LC50 273000 ppm	Rat	GESTIS

**Irritation and corrosivity**

Vapours may cause drowsiness and dizziness. After skin contact: Irritant.

**Additional information on tests**

The classification was carried out according to the calculation method of the Preparations Directive (1999/45/EC).

**SECTION 12: Ecological information****12.1. Toxicity**

Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

**12.3. Bioaccumulative potential****Partition coefficient n-octanol/water**

CAS No	Chemical name	Log Pow
74-98-6	propane	2,36
106-97-8	butane	2,89

**Further information**

Do not allow to enter into surface water or drains. The classification was carried out according to the calculation method of the Preparations Directive (1999/45/EC).

**SECTION 13: Disposal considerations****13.1. Waste treatment methods****Advice on disposal**

Do not allow to enter into surface water or drains. Dispose of waste according to applicable legislation.

**Waste disposal number of waste from residues/unused products**160504 WASTES NOT OTHERWISE SPECIFIED IN THE LIST; gases in pressure containers and discarded chemicals; gases in pressure containers (including halons) containing hazardous substances  
Classified as hazardous waste.**Waste disposal number of contaminated packaging**

150104 WASTE PACKAGING; ABSORBENTS, WIPING CLOTHS, FILTER MATERIALS AND PROTECTIVE CLOTHING NOT OTHERWISE SPECIFIED; packaging (including separately collected municipal packaging waste); metallic packaging

**Contaminated packaging**

Non-contaminated packages may be recycled. Handle contaminated packages in the same way as the substance itself.

**SECTION 14: Transport information****Land transport (ADR/RID)**

<b>14.1. UN number:</b>	UN1950
<b>14.2. UN proper shipping name:</b>	AEROSOLS
<b>14.3. Transport hazard class(es):</b>	2
Hazard label:	2.1

## Safety Data Sheet

according to Regulation (EC) No 1907/2006

## Kabelglide

Print date: 06.02.2017

Product code: 151

Page 6 of 7



Classification code: 5F  
Special Provisions: 190 327 625  
Limited quantity: 1 L  
Transport category: 2  
Tunnel restriction code: D

**Other applicable information (land transport)**

E0

**Inland waterways transport (ADN)**

**14.1. UN number:** UN1950  
**14.2. UN proper shipping name:** AEROSOLS  
**14.3. Transport hazard class(es):** 2  
Hazard label: 2.1



Classification code: 5F  
Special Provisions: 190 327 344 625  
Limited quantity: 1 L

**Other applicable information (inland waterways transport)**

E0

**Marine transport (IMDG)**

**14.1. UN number:** UN1950  
**14.2. UN proper shipping name:** AEROSOLS  
**14.3. Transport hazard class(es):** 2  
**14.4. Packing group:** -  
Hazard label: 2, see SP63

Special Provisions: 63, 190, 277, 327, 344, 959  
Limited quantity: See SP277  
EmS: F-D, S-U

**Other applicable information (marine transport)**

E0

**Air transport (ICAO)**

**14.1. UN number:** UN1950  
**14.2. UN proper shipping name:** AEROSOLS, flammable  
**14.3. Transport hazard class(es):** 2.1  
Hazard label: 2.1



Special Provisions: A145 A167  
Limited quantity Passenger: 30 kg G

**Safety Data Sheet**

according to Regulation (EC) No 1907/2006

**Kabelglide**

Print date: 06.02.2017

Product code: 151

Page 7 of 7

IATA-packing instructions - Passenger:	203
IATA-max. quantity - Passenger:	75 kg
IATA-packing instructions - Cargo:	203
IATA-max. quantity - Cargo:	150 kg

**Other applicable information (air transport)**E0  
: Y203**14.5. Environmental hazards**

ENVIRONMENTALLY HAZARDOUS: yes

**SECTION 15: Regulatory information****15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture****EU regulatory information**

2004/42/EC (VOC): 77,272 % (556,358 g/l)

**National regulatory information**

Water contaminating class (D): 2 - water contaminating

**SECTION 16: Other information****Relevant H and EUH statements (number and full text)**

H220	Extremely flammable gas.
H222	Extremely flammable aerosol.
H225	Highly flammable liquid and vapour.
H229	Pressurised container: May burst if heated.
H304	May be fatal if swallowed and enters airways.
H336	May cause drowsiness or dizziness.
H411	Toxic to aquatic life with long lasting effects.

*(The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)*