

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Multi

Print date: 11.01.2017

Product code: 116

Page 1 of 7

SECTION 1: Identification of the substance/mixture and of the company/undertaking**1.1. Product identifier**

Multi

1.2. Relevant identified uses of the substance or mixture and uses advised against**Use of the substance/mixture**

Lubricants, greases, release products

Uses advised against

Reserved for industrial and professional use.

1.3. Details of the supplier of the safety data sheet

Company name:	ITW LLC & Co. KG	
Street:	Mühlackerstrasse 149	
Place:	D-75417 Mühlacker	
Telephone:	++49(0)7041-96340	Telefax: ++49(0)7041-963429
e-mail:	info@itwcp.de	
Internet:	www.itwcp.de	
Responsible Department:	Produktsicherheit	

1.4. Emergency telephone number:++49(0)7041-96340
Mo. - Do. 8.00 - 16.30 Fr. 8.00 - 14.00**SECTION 2: Hazards identification****2.1. Classification of the substance or mixture****Regulation (EC) No. 1272/2008**

Hazard categories:

Aerosol: Aerosol 3

Hazard Statements:

Pressurised container: May burst if heated.

2.2. Label elements**Regulation (EC) No. 1272/2008****Signal word:** Warning**Hazard statements**

H229 Pressurised container: May burst if heated.

Precautionary statements

P251 Do not pierce or burn, even after use.

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.

Special labelling of certain mixtures

EUH066 Repeated exposure may cause skin dryness or cracking.

SECTION 3: Composition/information on ingredients**3.2. Mixtures**

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Multi

Print date: 11.01.2017

Product code: 116

Page 2 of 7

Hazardous components

CAS No	Chemical name			Quantity
	EC No	Index No	REACH No	
	Classification according to Regulation (EC) No. 1272/2008 [CLP]			
64742-48-9	Naphta heavy hydrogen treated			60-90%
	265-150-3			
	Asp. Tox. 1; H304			
124-38-9	Carbondioxide			5-10%
	204-696-9			
	Compressed gas; H280			
93820-57-6	Benzenesulfonic acid, di-C10-18-alkyl derivs., calcium salts			<1%
	298-637-4			
	Skin Irrit. 2, Aquatic Chronic 3; H315 H412			
9014-92-0	Poly(oxy-1,2-ethanediyl),a-(dodecylphenyl)-w-hydroxy-			<1%
	500-023-0			
	Acute Tox. 4, Eye Dam. 1, Aquatic Chronic 2; H302 H318 H411			
91-64-5	Cumarine			<1%
	202-086-7			
	Acute Tox. 4, Skin Sens. 1; H302 H317			

Full text of H and EUH statements: see section 16.

SECTION 4: First aid measures

4.1. Description of first aid measures

After inhalation

Provide fresh air.

After contact with skin

After contact with skin, wash immediately with: Water. Change contaminated clothing.

After contact with eyes

Rinse immediately carefully and thoroughly with eye-bath or water.

After ingestion

If swallowed, immediately drink: Water.

4.2. Most important symptoms and effects, both acute and delayed

No data available

4.3. Indication of any immediate medical attention and special treatment needed

No data available

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media

Co-ordinate fire-fighting measures to the fire surroundings.

Unsuitable extinguishing media

Water with tenside additive. Water.

5.2. Special hazards arising from the substance or mixture

Vapours may form explosive mixtures with air. Heating causes rise in pressure with risk of bursting.

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Multi

Print date: 11.01.2017

Product code: 116

Page 3 of 7

5.3. Advice for firefighters

In case of fire: Wear self-contained breathing apparatus.

Additional information

Use water spray jet to protect personnel and to cool endangered containers. Suppress gases/vapours/mists with water spray jet. Contaminated fire-fighting water must be collected separately. Do not allow to enter into surface water or drains.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Remove all sources of ignition. Provide adequate ventilation. Wear a self-contained breathing apparatus and chemical protective clothing.

6.2. Environmental precautions

Do not allow to enter into surface water or drains. Explosion hazard.

6.3. Methods and material for containment and cleaning up

Ventilate affected area.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Advice on safe handling

If handled uncovered, arrangements with local exhaust ventilation have to be used. Do not breathe gas/fumes/vapour/spray.

Advice on protection against fire and explosion

Keep away from sources of ignition. - No smoking.

7.2. Conditions for safe storage, including any incompatibilities

Requirements for storage rooms and vessels

Keep container tightly closed.

Advice on storage compatibility

Do not store together with: Material, rich in oxygen, oxidizing.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Exposure limits (EH40)

CAS No	Substance	ppm	mg/m ³	fibres/ml	Category	Origin
124-38-9	Carbon dioxide	5000	9150		TWA (8 h)	WEL
		15000	27400		STEL (15 min)	WEL

8.2. Exposure controls



Appropriate engineering controls

If handled uncovered, arrangements with local exhaust ventilation have to be used. Do not breathe gas/fumes/vapour/spray.

Protective and hygiene measures

Change contaminated clothing. Wash hands before breaks and after work. When using do not eat or drink.

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Multi

Print date: 11.01.2017

Product code: 116

Page 4 of 7

Eye/face protection

Tightly sealed safety glasses.

Hand protection

DIN EN 374 Tested protective gloves are to be worn: Butyl rubber. For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves.

Skin protection

Protective clothing:

Respiratory protection

In case of inadequate ventilation wear respiratory protection.

SECTION 9: Physical and chemical properties**9.1. Information on basic physical and chemical properties**

Physical state: Aerosol
Colour: light yellow
Odour: characteristic

Test method

Changes in the physical state**SECTION 10: Stability and reactivity****10.1. Reactivity**

No data available

10.2. Chemical stability

No data available

10.3. Possibility of hazardous reactions

No data available

10.4. Conditions to avoid

Keep away from heat. Ignition hazard.

10.5. Incompatible materials

No data available

10.6. Hazardous decomposition products

No data available

SECTION 11: Toxicological information**11.1. Information on toxicological effects****Acute toxicity**

CAS No	Chemical name	Exposure route	Dose	Species	Source
9014-92-0	Poly(oxy-1,2-ethanediyl),a-(dodecylphenyl)-w-hydroxy-	oral	ATE 500 mg/kg		
91-64-5	Cumarine	oral	ATE 500 mg/kg		

Additional information on tests

The classification was carried out according to the calculation method of the Preparations Directive (1999/45/EC).

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Multi

Print date: 11.01.2017

Product code: 116

Page 5 of 7

SECTION 12: Ecological information**Further information**

The classification was carried out according to the calculation method of the Preparations Directive (1999/45/EC).

SECTION 13: Disposal considerations**13.1. Waste treatment methods****Advice on disposal**

Dispose of waste according to applicable legislation.

Waste disposal number of waste from residues/unused products

160504 WASTES NOT OTHERWISE SPECIFIED IN THE LIST; gases in pressure containers and discarded chemicals; gases in pressure containers (including halons) containing hazardous substances
Classified as hazardous waste.

Waste disposal number of contaminated packaging

150104 WASTE PACKAGING; ABSORBENTS, WIPING CLOTHS, FILTER MATERIALS AND PROTECTIVE CLOTHING NOT OTHERWISE SPECIFIED; packaging (including separately collected municipal packaging waste); metallic packaging

Contaminated packaging

Water (with cleaning agent). Completely emptied packages can be recycled.

SECTION 14: Transport information**Land transport (ADR/RID)**

14.1. UN number: UN 1950
14.2. UN proper shipping name: AEROSOLS
14.3. Transport hazard class(es): 2
Hazard label: 2.2



Classification code: 5A
Special Provisions: 190 327 344 625
Limited quantity: 1 L
Transport category: 3
Tunnel restriction code: E

Other applicable information (land transport)

E0

Inland waterways transport (ADN)

14.1. UN number: UN 1950
14.2. UN proper shipping name: AEROSOLS
14.3. Transport hazard class(es): 2
Hazard label: 2.2



Classification code: 5A

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Multi

Print date: 11.01.2017

Product code: 116

Page 6 of 7

Special Provisions: 190 327 344 625
Limited quantity: 1 L

Other applicable information (inland waterways transport)
AEROSOLS

Marine transport (IMDG)

14.1. UN number: UN1950
14.2. UN proper shipping name: AEROSOLS
14.3. Transport hazard class(es): 2
14.4. Packing group: -
Hazard label: 2, see SP63

Special Provisions: 63, 190, 277, 327, 344, 959
Limited quantity: See SP277
EmS: F-D, S-U

Other applicable information (marine transport)
E0

Air transport (ICAO)

14.1. UN number: UN 1950
14.2. UN proper shipping name: AEROSOLS, non-flammable
14.3. Transport hazard class(es): 2.2
Hazard label: 2.2



Special Provisions: A98 A145 A167 A802
Limited quantity Passenger: 30 kg G
IATA-packing instructions - Passenger: 204
IATA-max. quantity - Passenger: 75 kg
IATA-packing instructions - Cargo: 204
IATA-max. quantity - Cargo: 150 kg

Other applicable information (air transport)
: Y204
E0
00000000005: Y203

14.5. Environmental hazards

ENVIRONMENTALLY HAZARDOUS: no

SECTION 15: Regulatory information**15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture****National regulatory information**

Water contaminating class (D): - - not water contaminating

SECTION 16: Other information**Relevant H and EUH statements (number and full text)**

H229 Pressurised container: May burst if heated.

**Safety Data Sheet**

according to Regulation (EC) No 1907/2006

Multi

Print date: 11.01.2017

Product code: 116

Page 7 of 7

H280	Contains gas under pressure; may explode if heated.
H302	Harmful if swallowed.
H304	May be fatal if swallowed and enters airways.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H411	Toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.
EUH066	Repeated exposure may cause skin dryness or cracking.

(The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)