

according to Regulation (EC) No 1907/2006

_		
Т	un	r

Print date: 10.01.2017

Product code: 104

Page 1 of 7

## SECTION 1: Identification of the substance/mixture and of the company/undertaking

## 1.1. Product identifier

Tuner

## 1.2. Relevant identified uses of the substance or mixture and uses advised against

## Use of the substance/mixture

Elekronikspray/Electronic Spray

### Uses advised against

Reserved for industrial and professional use.

#### 1.3. Details of the supplier of the safety data sheet

Company name: Street: Place:	ITW LLC & Co. KG Mühlackerstrasse 149 D-75417 Mühlacker	
Telephone: e-mail: Internet: Responsible Department:	++49(0)7041-96340 info@itwcp.de www.itwcp.de Produktsicherheit	Telefax:++49(0)7041-963429
<u>1.4. Emergency telephone</u> number:	++49(0)7041-96340 Mo Do. 8.00 - 16.30  Fr. 8.00 - 14.00	

## SECTION 2: Hazards identification

## 2.1. Classification of the substance or mixture

### Regulation (EC) No. 1272/2008

Hazard categories: Aerosol: Aerosol 1 Skin corrosion/irritation: Skin Irrit. 2 Serious eye damage/eye irritation: Eye Irrit. 2 Specific target organ toxicity - single exposure: STOT SE 3 Hazardous to the aquatic environment: Aquatic Chronic 2 Hazard Statements: Extremely flammable aerosol. Pressurised container: May burst if heated. Causes serious eye irritation. May cause drowsiness or dizziness. Toxic to aquatic life with long lasting effects.

#### 2.2. Label elements

### Regulation (EC) No. 1272/2008

## Hazard components for labelling

Isopropanol , Hydrocarbons,  $\overline{C}6$ , isoalkanes, <5% n-hexane

Signal word: Pictograms:

Danger



#### Hazard statements

H222	Extremely flammable aerosol.
H229	Pressurised container: May burst if heated.
H319	Causes serious eye irritation.
H336	May cause drowsiness or dizziness.



#### according to Regulation (EC) No 1907/2006

#### Tuner Print date: 10.01.2017 Product code: 104 Page 2 of 7 Toxic to aquatic life with long lasting effects. H411 **Precautionary statements** P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. P251 Do not pierce or burn, even after use. Keep away from heat. No Smoking. P210 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F. P410+P412 Avoid release to the environment. P273 Keep out of reach of children. P102

## **SECTION 3: Composition/information on ingredients**

## 3.2. Mixtures

#### Hazardous components

CAS No	Chemical name			Quantity
	EC No	Index No	REACH No	
	Classification according to Regulati	on (EC) No. 1272/2008 [CLP]		
64742-49-0	Naphtha (petroleum), hydrotreated light; Low boiling point hydrogen treated naphtha, <5% n-hexane			50-100 %
	931-254-9			
	Flam. Liq. 2, STOT SE 3, Asp. Tox. 1, Aquatic Chronic 2; H225 H336 H304 H411			
67-63-0	propan-2-ol; isopropyl alcohol; isopropanol			10-25%
	200-661-7	603-117-00-0		
	Flam. Liq. 2, Eye Irrit. 2, STOT SE 3; H225 H319 H336			
124-38-9	Carbondioxide			2,5-10%
	204-696-9			
	Compressed gas; H280			

Full text of H and EUH statements: see section 16.

#### **SECTION 4: First aid measures**

#### 4.1. Description of first aid measures

#### **General information**

No data available

#### After inhalation

Provide fresh air. In case of accident or unwellness, seek medical advice immediately (show directions for use or safety data sheet if possible).

#### After contact with skin

After contact with skin, wash immediately with: Water. Change contaminated clothing.

#### After contact with eyes

Rinse immediately carefully and thoroughly with eye-bath or water.

#### After ingestion

If swallowed, immediately drink: Water.

#### 4.2. Most important symptoms and effects, both acute and delayed

## No data available

# 4.3. Indication of any immediate medical attention and special treatment needed

No data available

#### **SECTION 5: Firefighting measures**



according to Regulation (EC) No 1907/2006

## Tuner

Print date: 10.01.2017

Product code: 104

Page 3 of 7

### 5.1. Extinguishing media

### Suitable extinguishing media

Carbon dioxide (CO2). Foam. Extinguishing powder.

## Unsuitable extinguishing media

Water with tenside additive. Water.

## 5.2. Special hazards arising from the substance or mixture

Combustible. Vapours may form explosive mixtures with air. Heating causes rise in pressure with risk of bursting.

### 5.3. Advice for firefighters

Wear a self-contained breathing apparatus and chemical protective clothing.

#### Additional information

Use water spray jet to protect personnel and to cool endangered containers. Suppress gases/vapours/mists with water spray jet. Contaminated fire-fighting water must be collected separately. Do not allow to enter into surface water or drains.

### **SECTION 6: Accidental release measures**

### 6.1. Personal precautions, protective equipment and emergency procedures

Remove all sources of ignition. Provide adequate ventilation. Wear a self-contained breathing apparatus and chemical protective clothing.

## 6.2. Environmental precautions

Do not allow to enter into surface water or drains. Explosion hazard.

## 6.3. Methods and material for containment and cleaning up

Ventilate affected area.

## **SECTION 7: Handling and storage**

## 7.1. Precautions for safe handling

#### Advice on safe handling

If handled uncovered, arrangements with local exhaust ventilation have to be used. Do not breathe gas/fumes/vapour/spray.

### Advice on protection against fire and explosion

Keep away from sources of ignition. - No smoking.

#### 7.2. Conditions for safe storage, including any incompatibilities

#### Requirements for storage rooms and vessels

Keep container tightly closed. Keep in a cool, well-ventilated place. Keep away from sources of ignition. - No smoking.

#### Advice on storage compatibility

Do not store together with: Material, rich in oxygen, oxidizing

## **SECTION 8: Exposure controls/personal protection**

## 8.1. Control parameters

#### Exposure limits (EH40)

CAS No	Substance	ppm	mg/m³	fibres/ml	Category	Origin
124-38-9	Carbon dioxide	5000	9150		TWA (8 h)	WEL
		15000	27400		STEL (15 min)	WEL
67-63-0	Propan-2-ol	400	999		TWA (8 h)	WEL
		500	1250		STEL (15 min)	WEL



according to Regulation (EC) No 1907/2006

## Tuner

Print date: 10.01.2017

Product code: 104

Page 4 of 7

## 8.2. Exposure controls





## Appropriate engineering controls

If handled uncovered, arrangements with local exhaust ventilation have to be used. Do not breathe gas/fumes/vapour/spray.

### Protective and hygiene measures

Remove contaminated, saturated clothing immediately. Protect skin by using skin protective cream. After work, wash hands and face. When using do not eat or drink.

### Eye/face protection

Tightly sealed safety glasses.

## Hand protection

DIN EN 374 Tested protective gloves are to be worn: Butyl rubber. For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves.

### Skin protection

Protective clothing:

## **Respiratory protection**

In case of inadequate ventilation wear respiratory protection.

## **SECTION 9: Physical and chemical properties**

## 9.1. Information on basic physical and chemical properties

Physical state: Colour: Odour:	Aerosol colourless characteristic		
		Test metho	d
Changes in the physical state			
Initial boiling point and boiling range:		60 °C	
Flash point:		< 0 °C	
Lower explosion limits:		1,2 vol. %	
Upper explosion limits:		7 vol. %	
Ignition temperature:		300 °C	
Vapour pressure: (at 20 °C)		227 hPa	
Vapour pressure: (at 50 °C)		719 hPa	
Density (at 20 °C):		0,68 g/cm³	
Solvent content:		90%	

## **SECTION 10: Stability and reactivity**

#### 10.1. Reactivity

No data available

## 10.2. Chemical stability

No data available



## according to Regulation (EC) No 1907/2006

#### Tuner

Print date: 10.01.2017

Product code: 104

Page 5 of 7

## 10.3. Possibility of hazardous reactions

No data available

## 10.4. Conditions to avoid

Keep away from heat. Ignition hazard.

10.5. Incompatible materials

No data available

## 10.6. Hazardous decomposition products

No data available

## **SECTION 11: Toxicological information**

#### 11.1. Information on toxicological effects

#### Irritation and corrosivity

Vapours may cause drowsiness and dizziness. After skin contact: Irritant.

#### Additional information on tests

The classification was carried out according to the calculation method of the Preparations Directive (1999/45/EC).

#### **SECTION 12: Ecological information**

## 12.1. Toxicity

Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

#### **Further information**

Do not allow to enter into surface water or drains. The classification was carried out according to the calculation method of the Preparations Directive (1999/45/EC).

### **SECTION 13: Disposal considerations**

## 13.1. Waste treatment methods

#### Advice on disposal

Do not allow to enter into surface water or drains. Dispose of waste according to applicable legislation.

#### Waste disposal number of waste from residues/unused products

160504 WASTES NOT OTHERWISE SPECIFIED IN THE LIST; gases in pressure containers and discarded chemicals; gases in pressure containers (including halons) containing hazardous substances Classified as hazardous waste.

## Waste disposal number of contaminated packaging

150104 WASTE PACKAGING; ABSORBENTS, WIPING CLOTHS, FILTER MATERIALS AND PROTECTIVE CLOTHING NOT OTHERWISE SPECIFIED; packaging (including separately collected municipal packaging waste); metallic packaging

### Contaminated packaging

Non-contaminated packages may be recycled. Handle contaminated packages in the same way as the substance itself.


#### **SECTION 14: Transport information**

#### Land transport (ADR/RID)

14.1. UN number:	UN1950
14.2. UN proper shipping name:	AEROSOLS
14.3. Transport hazard class(es):	2
Hazard label:	2.1



## according to Regulation (EC) No 1907/2006





## according to Regulation (EC) No 1907/2006

Tuner				
Print date: 10.01.2017		Product code: 104		Page 7 of 7
IATA-packing instructions - F	Passenger:	203		
IATA-max. quantity - Passen	iger:	75 kg		
IATA-packing instructions - C	Cargo:	203		
IATA-max. quantity - Cargo:		150 kg		
Other applicable informatic E0 : Y203	on (air transpo	ort)		
14.5. Environmental hazards				
ENVIRONMENTALLY HAZA	RDOUS:	yes	¥2	
Danger releasing substance	:	Hydrocarbons		
SECTION 15: Regulatory in	formation			
15.1. Safety, health and enviro	nmental regul	ations/legislation specific for the	he substance or mixture	
EU regulatory information				
2004/42/EC (VOC):		75 % (510 g/l)		
National regulatory informa	ation			
Water contaminating class (I	D):	2 - water contaminating		
SECTION 16: Other information				
Relevant H and EUH statements (number and full text)				
H222 Extremely flammable aerosol.				
	Highly flammable liquid and vapour.			
	Pressurised container: May burst if heated.			
		nder pressure; may explode if hea	ated.	
	lay be fatal if s auses serious	wallowed and enters airways.		
		vsiness or dizziness.		
	•	life with long lasting effects.		

(The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)