



A Donaldson Company

A WORLD LEADER IN FUME
EXTRACTION TECHNOLOGY

LASER FUME EXTRACTION **ADVANTAGE RANGE**





BOFA INTERNATIONAL IS A MULTI AWARD-WINNING WORLD LEADER IN PORTABLE FUME EXTRACTION AND FILTRATION TECHNOLOGY.

We design, develop and manufacture systems for a wide range of industrial sectors and applications.

Our products ensure operator safety by capturing harmful dust and fumes which are generated during industrial processes while minimising disruption to production.

WHY BOFA

- ✓ Over 30 years' **experience**
- ✓ Market **leader**
- ✓ **Unrivalled** expertise in fume and dust extraction and filtration
- ✓ **Innovative** world-class solutions
- ✓ High **quality**, affordable systems
- ✓ Developed by **experts**
- ✓ **Dedicated** in house capabilities
- ✓ Offices in the **UK, USA** and **Germany**
- ✓ **Global** network of distributors
- ✓ Keeping the world working **safely**
- ✓ Continual **investment**
- ✓ **Environmental** policy
- ✓ A **Donaldson** company

BOFA is proud to be a Donaldson company. Founded in 1915, Donaldson is a global leader in the filtration industry with sales, manufacturing and distribution locations around the world.





MARKET LEADING **TECHNOLOGY**

We are recognised as the market leader, delivering great value, high quality products.

Many years of designing and manufacturing fume extraction and filtration systems for a wide range of industries has given BOFA the experience and expertise to ensure that our product solutions are the best available on the market. We have applied our in-depth understanding of industrial processes and applications into the design and manufacture of our products.

THE FUTURE FOR FUME EXTRACTION **IS TRULY GLOBAL**

The need for fume extraction continues to be inherently linked with Health and Safety laws and compliance. Within the developed western markets such legislation is well defined and in the main compliance levels are high.

Most encouraging is the growing trend for improved employee welfare and environmental responsibility in regions where historically there has been less regard for either. This is a welcome and significant step change for our planet, and one that at the macro level will drive an even greater demand for fume extraction.

EXPERTISE **AND INNOVATION**

Our dedicated team has a wealth of knowledge and unrivalled expertise within our field which is established and trusted by all sizes of business, from global market leaders to niche producers in a wide cross section of industries.

Innovation is at the heart of everything we do, meaning we develop the most technically advanced products on the market. But we also have the flexibility to develop bespoke solutions to suit our customers' requirements. Our programme of ongoing investment in research and development allows us to continuously improve products and pioneer new cutting-edge technologies, bringing the best and latest developments to our portfolio.



QUALITY **MANUFACTURING**

Our philosophy is to maintain control of supply and quality standards throughout the entire manufacturing process of our products. We have an extensive range of proven fume extraction solutions to satisfy a broad range of applications - from single user systems to units that pack a heavyweight punch with unsurpassed filter capacity, high performance and everything inbetween. All made to the highest international manufacturing standards.

AWARD WINNING TECHNOLOGY

BOFA is awarded the Queen's Award for Enterprise 2017 for Innovation!

In 2017 we were awarded the Queen's Award for Enterprise: Innovation for our revolutionary Intelligent (iQ) Operating System, which is transforming the way that organisations around the world are able to protect the health of employees and improve production processes. See page 9 for more information.

Our Queen's Award for International Trade in 2012, recognises that over 90% of our products are now exported overseas.



We are proud to have won awards for innovation, export and business.



INTELLIGENT (iQ2) OPERATING SYSTEM



The next generation of fume extraction technology is here!

The huge success of BOFA's unique Intelligent (iQ) Operating System established a step change in fume extraction technology. It takes performance and safety parameters to a new level and ensures maintenance downtime and ownership costs are kept to a minimum. See page 8 for more information on this award-winning technology.

iQ2 builds on this, adding significantly to the list of seller and user benefits. It combines field proven iQ reliability with a range of new and highly advanced feature enhancements, including Fieldbus connectivity; two-way communication and control; and SMART filter technology.



INDUSTRY 4.0

Driven by Industry 4.0, iQ2 meets tomorrow's needs, today, keeping you and your customers ahead in the market.

It incorporates Fieldbus connectivity, making it easy to integrate into existing factory systems and the intuitive interface makes it simple to use. By connecting machines, businesses can create intelligent networks along the entire value chain that can control each other autonomously. Remote monitoring and internal control can be achieved thanks to the unique two-way data streaming capabilities. Systems self-analyse to enable predictability, providing management with more insight on the status of the factory and allowing interventions, such as filter changes, to take place at the best possible time – achieving just-in time maintenance and near zero downtime.

All this combines to deliver an enhanced user experience:

- Built on proven BOFA iQ technology
- Fieldbus connectivity
- Two-way communication and control
- Hi-resolution colour touch screen display
- Customisable – including multi language navigation and bespoke branding
- Effective filter monitoring, providing accurate filter life prediction
- Live remote monitoring for greater control
- Real-time capability to collect and analyse data
- Fully configurable alarms and warnings
- Advanced reporting tools for better support
- SMART filter technology as an optional extra
- Simple software updates, making it futureproof



SMART FILTER TECHNOLOGY

Improve filter performance. Incorporating proven RFID technology, each SMART filter has a uniquely coded non-removable tag, allowing the iQ2 operating system to establish authenticity and suitability of the filter being used. SMART filter technology provides the end user with the added safety assurance that they are using a proprietary filter of the right type for their application and chosen extraction unit.

SMART filter technology is an optional extra*



SMART FILTER TECHNOLOGY

* See SMART filter technology featured on our AD Oracle iQ2 on page 23.

For assured filter performance:

- iQ2 system integration
- Anti-tamper RFID technology
- Correct filter detection
- Enhanced data collection
- Remote filter monitoring

For enhanced filter experience:

- Legislative compliance
- Reduced cost of ownership
- Superior filter performance
- Optimised running time
- Planned maintenance scheduling

For trouble free filter ownership:

- Ensures the highest yield
- Protected performance
- Genuine filter programme
- Remote filter management

THE FUTURE ORACLE 2

Our new Oracle 2 brings a host of additional benefits. With a fresh new look, it has new features designed to meet the increased performance and standards of today's manufacturing environment

- CleanChange - our new filter housing facilitates cleaner filter changes, leaving you with a cleaner unit and working environment, coupled with reduced contamination when swapping out filters
- Larger filters - improve filter life, saving you money and time changing filters
- Multiple power leads make this a truly universal product with one part number the world over
- Quieter - with an optional noise reduction system.

What's more, it will come with iQ2 as standard, making this the most advanced fume extraction unit on the market.



INTELLIGENT (iQ) OPERATING SYSTEM




Pioneering fume extraction.

Our award-winning Intelligent (iQ) Operating System brings multiple performance enhancements for higher efficiency of extraction, individual filter status monitoring and integral design features that combine to deliver a lower cost of ownership.

Most importantly, the iQ addresses the issue dreaded by most production teams - downtime - by minimising the potential for interrupting production for unplanned filter changes.

Sophisticated and advanced technology is inbuilt, providing a user-friendly and intuitive experience with the data being easy to access and analyse locally or remotely (from data downloaded via USB). It means that filter changes can be planned at a time to minimise or eliminate interruptions to production so businesses can continue as usual, as well as helping to avoid any costly or time-consuming service call-outs.



The iQ Operating System incorporates a method for monitoring the status of both the pre filter and combined (main) filter. Pre blockage warnings provide operators with ample time to prepare for a change by identifying which filter needs replacing and when so the uncertainty and guesswork is removed.

A user-friendly design is consistent across all iQ products for a more uniform look in environments where multiple units are in use. The operating 'easy read' control panel is on the top of each unit on a sloping fascia front so the data is easy to view.

DEEPPLEAT DUO

PRE FILTER




Save filter life and money.

The DeepPleat DUO is the longest lasting pre filter available on the market, extending the life of your main filter and reducing the overall cost of ownership of your unit.

BOFA's unique patent-protected DeepPleat DUO pre filter technology is designed to maximise filter life. It incorporates a large capacity drop-out chamber within the filter, along with an impressive surface area above the chamber to deal with a high volume and variety of particulate, ensuring optimised performance and filter life. Within the housing there is a sealed 200mm deep pleat layer of F8 media giving a surface area in excess of 6;12; and 30 sq metres.

Thanks to a specially moulded grommet style gasket situated within the drop out chamber the DeepPleat DUO is designed for easy and safe installation and replacement, which is particularly important as often harmful contaminants are captured within the filter.



The DeepPleat DUO is available in three different sizes, offering different drop-out chamber sizes and surface medium areas:

Product	Inlet size	Dropout chamber size	Surface media area	Filter media pleat size
AD Nano (+)	50mm	7.44 litres	6m ²	150mm
AD Oracle iQ	75mm	16.2 litres	12m ²	200mm
AD 500/1000/1500 iQ	125mm	58 litres	30m ²	200mm
AD 2000 iQ	125mm	58 litres x2 (116 litres)	30m ² x2 (60m ²)	200mm x2 (400mm)
AD 4000 iQ	125mm	58 litres x3 (174 litres)	30m ² x3 (90m ²)	200mm x3 (600mm)

Throughout this brochure you will see icons next to products to show their key features:



Intelligent (iQ2) Operating System

iQ2 combines field proven iQ reliability with a range of new and highly advanced feature enhancements, including Fieldbus connectivity, two-way communication and control, and SMART filter technology. See page 6 for more information.

Find out more: bofainternational.com/iq2



Intelligent (iQ) Operating System

Our patent-protected award-winning Intelligent (iQ) Operating System performs at two distinct levels: operators benefit from the ease of operation and clarity of real time information and the system provides a cache of analytical data, enabling users to download performance and operating parameters for evaluation purposes. See page 9 for more information.

Find out more: bofainternational.com/iq



DeepPleat pre filter

The DeepPleat pre filter consists of a pleated filter of 100mm depth or greater, allowing for increased surface area within a smaller area. This means BOFA filters last a long time and do not take up a large footprint.

Find out more: bofainternational.com/deeppleat



DeepPleat DUO pre filter

Our patent-protected DeepPleat DUO pre filter technology is designed to maximise filter life. It incorporates a large capacity drop-out chamber within the filter. Above this chamber is an impressive surface area to deal with high volumes and variety of particulate, ensuring optimised performance and filter life.

The DeepPleat DUO is designed for easy and safe installation and replacement, which is particularly important as often harmful contaminants are captured within the filter. See page 10 for more information

Find out more: bofainternational.com/deeppleatduo



HEPA filter

Removes 99.997% of particles at 0.3 micron in size.

Find out more: bofainternational.com/hepa



ACF: Advanced carbon filter

ACF assures safe capture and removal of hazardous fumes. Contaminated air must remain in contact with the carbon bed for a period of time sufficient to ensure that no contaminants or odours are emitted (dwell time). Our design considers the balance between airflow rates and the type, depth and surface area of the carbon used to ensure suitability for the contaminants associated with the application and to ensure appropriate dwell times are achieved.

Our filters have been developed to capture contaminants and odours, eliminating the risk of bypass and/or tunnelling.

Find out more: bofainternational.com/acf



AFC: Automatic flow control

AFC allows the operator to preset correct airflow rates for the specific application, subsequently maintaining this airflow. This generates lower noise levels and ensures further protection of HEPA filters.

Find out more: bofainternational.com/afc



SFT: SMART filter technology

The new SMART filter system works with iQ2 to give assured filter performance. It incorporates RFID technology, so each filter has a uniquely coded, non removable label, allowing the iQ2 Operating System to establish authenticity and suitability.

Find out more: bofainternational.com/sft



RFA: Reverse flow air technology

RFA enhances filter performance and ensures longer filter life. It causes a fall in velocity and air direction change. Larger particulate falls out of the airstream into the drop out chamber. With less particulate entering the filter media the filter life is significantly increased. Contaminated air entering the drop out chamber is pulled vertically through the filters.

Find out more: bofainternational.com/rfa



MVS: Multi voltage sensing unit

Our MVS units automatically sense local voltage and automatically operate between 90-257V, for global use.



PATENTED technology

We invest in innovation and our products have a heritage of being tried, tested and trusted. We take great care in protecting our intellectual property and our integrity. Our product range includes aspects which are protected under patent copyright, design copyright, registered design and trade mark laws.



SureCHECK quality standard

In recognition of the importance of quality, health and safety and environmental management, we have created our own stringent SureCHECK quality standard, applied to every product we make.

Find out more: bofainternational.com/surecheck




ProTECT

Our ProTECT service plan gives you peace of mind that your LEV systems are being expertly maintained throughout their working life.

Find out more: bofainternational.com/protect

Technical information in this brochure is correct at time of publishing. Please contact us for details.



BOFA's ADVANTAGE range of laser fume extraction and filtration systems are designed for applications that generate particulate and gaseous volatile organic compounds (VOCs) within the laser coding, marking, cutting and engraving industries. Our Base units have been designed so that a number of manufacturer's laser engravers can sit on top of the extractor, effectively, doubling up as a work station.

LASER FUME EXTRACTION

ADVANTAGE RANGE

By maintaining a dust-free operating area, our systems help to protect valuable equipment, maintain a higher quality mark and reduce the number of rejects and contaminants.

APPLICATIONS

Traceability and date codes

Deep laser engraving

Laser coding

Laser marking

Laser drilling

Laser cutting

Laser welding

Laser etching

Laser engraving

Laser micro-machining

Web scoring

Laser perforating

Laser cleaning

Laser kiss cutting

Laser pairing





AD ACCESS

A compact system for light duty laser marking, coding and engraving applications. The AD Access combines economic ownership with performance to match the small laser user, ensuring safe operator working conditions and product quality.

A three-stage filter condition indicator is included as a standard feature.

Approvals CE | cUL | UL

For full product features - see page 39.

Dimensions 505 x 335 x 315mm
19.88 x 13.19 x 12.40"

Airflow/Pressure 180m³/hr / 30mbar
106cfm / 30mbar

Technology



Datasheet download

bofainternational.com/ad-access

OUR LEADING
TECHNOLOGY



iQ2
Intelligent (iQ2)
Operating System



iQ
Intelligent (iQ)
Operating System



DeepPleat
DeepPleat
pre filter



DeepPleat DUO
DeepPleat DUO
pre filter



HEPA
HEPA filter



ACF
Advanced carbon
filter technology

AD FUSION

The AD Fusion has been designed to work with the new generation of low cost laser systems. It provides high performance at affordable prices and is ideally matched with smaller laser systems.

Approvals CE

For full product features - see page 39.



Dimensions 590 x 380 x 440mm
23.2 x 38.6 x 17.3"

Airflow/Pressure 285m³/hr / 24mbar
167cfm / 24mbar

Technology



Datasheet download
bofainternational.com/ad-fusion





AD 250

The AD 250 provides a cost effective solution for light duty applications. This compact and extremely quiet system is ideal for use in schools, sign making workshops, small scale industrial environments and light laser coding applications.

Approvals CE | cUL | UL

For full product features - see page 39.

Dimensions 570 x 405 x 465mm
23.23 x 15.94 x 18.31"

Airflow/Pressure 180m³/hr / 30mbar
106cfm / 30mbar

Technology



Datasheet download
bofainternational.com/ad-250

OUR LEADING
TECHNOLOGY



iQ2
Intelligent (iQ2)
Operating System



iQ
Intelligent (iQ)
Operating System



DeepPleat
DeepPleat
pre filter



DeepPleat DUO
DeepPleat DUO
pre filter



HEPA
HEPA filter



ACF
Advanced carbon
filter technology

AD 350

The quiet and compact AD 350 effectively removes potentially harmful fumes and particulate created during light duty laser marking, coding and engraving applications making it ideal for use in schools, sign making workshops and small scale industrial environments.

Approvals CE | cUL | UL

For full product features - see page 39.



Dimensions 570 x 405 x 465mm
23.23 x 15.94 x 18.31"

Airflow/Pressure 380m³/hr / 96mbar
223cfm / 96mbar

Technology



Datasheet download
bofainternational.com/ad-350





AD NANO

The AD Nano is ideal for small scale industrial environments and light to medium laser coding applications. The reverse flow air technology enhances filter performance and ensures longer filter life, with its DeepPleat DUO filter technology.

Approvals CE

For full product features - see page 39.

Dimensions 790 x 360 x 420mm
31.1 x 14.17 x 16.54"

Airflow/Pressure 170m³/hr / 30mbar
100cfm / 30mbar

Technology



Datasheet download

bofainternational.com/ad-nano

OUR LEADING
TECHNOLOGY



iQ2
Intelligent (iQ2)
Operating System



iQ
Intelligent (iQ)
Operating System



DeepPleat
DeepPleat
pre filter



DeepPleat DUO
DeepPleat DUO
pre filter



HEPA
HEPA filter




ACF
Advanced carbon
filter technology

AD NANO+

This compact 'go anywhere' fume extraction system is feature-packed for big performance in small scale industrial sites and light laser coding applications. Incorporating many of the features found on our larger systems, the AD Nano+ is a cost effective solution for light to medium duty applications, making it the ideal choice for installations where floor space is limited.

The use of an auto-voltage sensing turbine means that this unit can be used anywhere in the world.

Approvals CE

Dimensions	790 x 360 x 420mm 31.1 x 14.17 x 16.54"
Airflow/Pressure	300m ³ /hr / 96mbar 176cfm / 96mbar
Technology	
<p>Datasheet download bofainternational.com/ad-nano-plus</p>	



For full product features - see page 39.

AD UNIVERSAL

This compact system is ideal for light to medium small scale industrial environments.

Approvals CE

For full product features - see page 39.



Dimensions	625 x 385 x 525mm 24.61 x 15.16 x 20.67"
Airflow/Pressure	380m ³ /hr / 96mbar 223cfm / 96mbar

Technology



Datasheet download

bofainternational.com/ad-universal

OUR LEADING
TECHNOLOGY



iQ2
Intelligent (iQ2)
Operating System



iQ
Intelligent (iQ)
Operating System



DeepPleat
DeepPleat
pre filter



DeepPleat DUO
DeepPleat DUO
pre filter



HEPA
HEPA filter



ACF
Advanced carbon
filter technology

AD ORACLE SA iQ

This compact laser fume extractor incorporates a powerful range of unique features into one unit. It uses a smaller pre filter to the AD Oracle iQ, but includes all the other features, making it ideal for lighter use applications.

Approvals CE | cUL | UL

For full product features - see page 39.



Dimensions 730 x 430 x 515mm
 28.7 x 17 x 20.3"

Airflow/Pressure 380m³/hr / 96mbar
 223cfm / 96mbar

Technology



Datasheet download

bofainternational.com/ad-oracle-sa-iq





AD ORACLE iQ

The AD Oracle iQ combines a powerful range of unique features into one compact unit. This versatile system can be used across a range of laser applications and the revolutionary auto-voltage sensing blower automatically self adjusts to run on any voltage worldwide.

Our inline AD Cyclone (page 36) has been designed to separate lower particle sizes during laser marking process.

Approvals CE | cUL | UL

Also fits the FireBox MA and FireBox GA

- See page 37 for further information.

Dimensions 975 x 455 x 505mm
38.39 x 17.91 x 19.88"

Airflow/Pressure 380m³/hr / 96mbar
223cfm / 96mbar

Technology



Datasheet download

bofainternational.com/ad-oracle-iq

For full product features - see page 39.

OUR LEADING
TECHNOLOGY



iQ2
Intelligent (iQ2)
Operating System



iQ
Intelligent (iQ)
Operating System



DeepPleat
DeepPleat
pre filter



DeepPleat DUO
DeepPleat DUO
pre filter



HEPA
HEPA filter



ACF
Advanced carbon
filter technology

AD ORACLE iQ2

The next generation of fume extraction, the AD Oracle iQ2 combines field proven iQ technology with a range of new and highly advanced features, including Fieldbus connectivity, two-way communication and control, accurate filter monitoring - to ensure maximum lifespan and no unplanned maintenance - and remote reporting and diagnostics.

It can be used across a wide range of laser applications, with the option to have SMART filters.

See pages 6-7 for more information about iQ2 and SMART filter technology.

Our inline AD Cyclone (page 36) has been designed to separate lower particle sizes during laser marking process.

Approvals CE

Also fits the FireBox MA and FireBox GA
- See page 37 for further information.

NEW



Dimensions 982 x 470 x 516mm
38.66 x 18.5 x 20.3"

Airflow/Pressure 380m³/hr / 96mbar
223cfm / 96mbar

Technology



Datasheet download
bofainternational.com/ad-oracle-iq2

For full product features - see page 39.

LASER FUME EXTRACTION ADVANTAGE RANGE



AD 500 iQ | 1000 iQ | 1500 iQ

These mid to high end laser fume extraction systems combine extremely large filter capacity with high airflow and pressure rates, making them the ideal choice for heavy duty applications that generate large amounts of particulate and gaseous organic compounds.

Performance has been further enhanced with the inclusion of several features including BOFA's acclaimed patented iQ Operating System.

Approvals CE | cUL | UL

AD 500 iQ / 1000 iQ / 1500 iQ fits the FireBox MA+ and FireBox GA+
- See page 37.

For full product features - see page 39.

Dimensions	1205 x 615 x 790mm 47.44 x 24.21 x 31.1"
AD 500 iQ Airflow/Pressure	550m ³ /hr / 100mbar 324cfm / 100mbar
AD 1000 iQ Airflow/Pressure	850m ³ /hr / 100mbar 500cfm / 100mbar
AD 1500 iQ Airflow/Pressure	1250m ³ /hr / 100mbar 735cfm / 100mbar

Technology



Datasheet download

bofainternational.com/ad-500-iq
bofainternational.com/ad-1000-iq
bofainternational.com/ad-1500-iq

OUR LEADING
TECHNOLOGY



iQ2
Intelligent (iQ2)
Operating System



iQ
Intelligent (iQ)
Operating System



DeepPleit
DeepPleit
pre filter



DeepPleit DUO
DeepPleit DUO
pre filter



HEPA
HEPA filter



ACF
Advanced carbon
filter technology

AD 2000 iQ

The AD 2000 iQ's technology delivers superior and measurable performance, ensuring airflow and filtration is maintained even when particulates start to build up. The dual filter system creates maximum capacity while the three-stage filtration process ensures peak performance. This makes it suitable for the most demanding and complex installations, so you can rely on extended filter life, together with effective removal of fumes and particulates.

It's user friendly too, with a design that makes easy work of filter changes. The easy to read and access control display panel is conveniently located on top of the unit.

The AD 2000 iQ's design also permits greater flexibility of different exhaust installations and different configurations allowing recirculation via the rear panel or externally vented hose connection systems.

Approvals CE

For full product features - see page 39.



Dimensions 1277 x 1318 x 1013mm
50.3 x 51.9 x 39.9"

Airflow/Pressure 2500m³/hr / 96mbar
1295cfm / 96mbar

Technology



Datasheet download

bofainternational.com/ad-2000-iq





AD 4000 iQ

The AD 4000 iQ delivers superior and measurable performance, ensuring airflow and filtration is maintained even when particulates start to build up from the triple DeepPleat DUO and combined filter setup. This makes it suitable for the most demanding and complex installations, so you can rely on extended filter life, together with effective removal of fumes and particulates.

For full product features - see page 39.

Dimensions 1300 x 1955 x 1100mm
51.18 x 76.97 x 43.31"

Airflow/Pressure 3600m³/hr / 44mbar
2119cfm / 44mbar

Technology



Datasheet download

bofainternational.com/ad-4000-iq

It's user friendly too, with a design that makes easy work of filter changes. The easy to read and access control display panel is conveniently located on top of the unit.

The AD 4000 iQ's design also permits greater flexibility of different exhaust installations. Different exhaust configurations allow recirculation via the rear panel or externally vented hose connection systems.

Approvals CE

OUR LEADING
TECHNOLOGY



iQ2
Intelligent (iQ2)
Operating System



iQ
Intelligent (iQ)
Operating System



DeepPleat
DeepPleat
pre filter



DeepPleat DUO
DeepPleat DUO
pre filter



HEPA
HEPA filter



ACF
Advanced carbon
filter technology

AD 4000

The AD 4000 laser fume extraction unit combines large filter capacity with high airflows. This combination makes the AD 4000 ideal for large laser engravers, laser cutters as well as multiple laser coding installations.

Easily accessible filters are accommodated by the uniquely styled gas spring assisted 'gull winged' doors, which allow for maximum space and ease when changing filters.

Unit interfaces such as stop/start and system failure are available as options.

Approvals CE

Dimensions 1475 x 1450 x 1500mm
50.2 x 76.7 x 43.3"

Airflow/Pressure 4000m³/hr / 30mbar
2354cfm / 30mbar

Technology




Datasheet download
bofainternational.com/ad-4000



For full product features - see page 39.





AD PVC iQ

The AD PVC iQ extraction system has been designed to effectively deal with the corrosive nature of the fumes generated when lasering PVC materials.

The latest design specification includes many of the features associated with our AD Oracle iQ (page 22) model as standard but in addition all internally exposed surfaces have been coated to resist the corrosive nature of the fume and each unit is fitted with HCL and VOC sensors which continually monitor the exhaust air of the unit giving added safety assurance.

Approvals CE | cUL | UL

Dimensions 1090 x 570 x 600mm
42.91 x 22.44 x 23.62"

Airflow/Pressure 350m³/hr / 96mbar
206cfm / 96mbar

Technology



Datasheet download

bofainternational.com/ad-pvc-iq

For full product features - see page 39.

OUR LEADING
TECHNOLOGY



iQ2
Intelligent (iQ2)
Operating System



iQ
Intelligent (iQ)
Operating System



DeepPleat
DeepPleat
pre filter



DeepPleat DUO
DeepPleat DUO
pre filter



HEPA
HEPA filter



ACF
Advanced carbon
filter technology

AD GoldSEAL + Cyclone

This unit offers the complete solution for the extraction, filtration and recovery of precious metals. The particles are collected in an easy to remove tray and the HEPA filter can be incinerated to reveal the precious metal collected during the filtration process.

Automatic flow control allows the user to pre-set correct airflow rates, for lower noise levels and further protection of the HEPA filter. The cyclone enables the separation of precious metals before they even reach the main extraction area, allowing for easier and more efficient collection, as well as prolonging the life of the main filter.

Approvals CE

For full product features - see page 39.



Dimensions 755 x 650 x 560mm
29.72 x 25.60 x 22.05"

Airflow/Pressure 267m³/hr / 96mbar
157cfm / 96mbar

Technology



Datasheet download

bofainternational.com/ad-goldseal-plus-cyclone



RFA
Reverse flow air
technology



AFC
Automatic flow
control technology



SFT
SMART filter
technology



MVS
Multi voltage
sensing unit



PATENTED
Patented
technology



SureCHECK
SureCHECK quality
standard



PROTECT
ProTECT service
plan

AD Base 1 Oracle



Suitable for a range of lasers, the AD Base 1 Oracle combines a DeepPleat DUO pre filter and auto-voltage blower in a compact base system. BOFA's easi-seal filter location makes filter change easy, quick and safe.

As with all our Base systems, this unit has the option of an onboard compressor for a compact installation.

Approvals CE

For full product features - see page 39.

Dimensions 7905 x 735 x 740mm
31.1 x 28.94 x 29.13"

Airflow/Pressure 380m³/hr / 96mbar
223cfm / 96mbar

Technology



Datasheet download

bofainternational.com/ad-base-1-oracle

OUR LEADING
TECHNOLOGY



iQ2
Intelligent (iQ2)
Operating System



iQ
Intelligent (iQ)
Operating System



DeepPleat
DeepPleat
pre filter



DeepPleat DUO
DeepPleat DUO
pre filter



HEPA
HEPA filter



ACF
Advanced carbon
filter technology

AD Base 2 Oracle

Adapting the AD Base 1 Oracle, this unit sits lower to allow larger bed lasers to be placed securely on top whilst giving a direct extraction system. This system also benefits from a DeepPleat DUO pre filter and multi voltage sensing unit.

As with all our Base systems, this unit has the option of an onboard compressor for a compact installation.



Approvals CE

For full product features - see page 39.

Dimensions 550 x 1060 x 810mm
21.65 x 41.74 x 31.89"

Airflow/Pressure 380m³/hr / 96mbar
223cfm / 96mbar

Technology



Datasheet download

bofainternational.com/ad-base-2-oracle



AD Base 3

The AD Base 3 is designed for the smaller Universal Versa Laser. The optional onboard compressor makes this a compact installation.

Approvals CE

For full product features - see page 39.



Dimensions 775 x 510 x 680mm
30.51 x 20.08 x 26.77"

Airflow/Pressure 180m³/hr / 30mbar
105cfm / 30mbar

Technology



Datasheet download

bofainternational.com/ad-base-3

OUR LEADING
TECHNOLOGY



iQ2
Intelligent (iQ2)
Operating System



iQ
Intelligent (iQ)
Operating System



DeepPleat
DeepPleat
pre filter



DeepPleat DUO
DeepPleat DUO
pre filter



HEPA
HEPA filter



ACF
Advanced carbon
filter technology

AD Base C180

Bespoke unit tailored to match the GCC C180 laser engraver. The dimensions of the unit allow the C180 to fit perfectly onto the extractor, effectively doubling it up as a work station. The unit is also offered with an onboard air compressor to provide the laser with its air assist requirements and comes complete with extraction hose kit and compressor link up on compressor models.

Approvals CE

For full product features - see page 39.



Dimensions 795 x 720 x 675mm
31.3 x 28.3 x 26.6"

Airflow/Pressure 180m³/hr / 30mbar
105cfm / 30mbar

Technology



Datasheet download

bofainternational.com/ad-base-c180





AD Base Z

The AD Base Z has been designed specifically for the Epilog Zing laser engraver. The dimensions of the unit allow the Zing to fit perfectly onto the extractor, effectively doubling it up as a work station. The distinctive blue finish has been matched with the blue ends of the laser to give a stylish installation.

The unit is also offered with an onboard air compressor to provide the laser with its air assist requirements. All units come complete with extraction hose kit and compressor link up on compressor models.

Approvals CE

Dimensions	780 x 780 x 600mm 30.71 x 30.71 x 23.62"
Airflow/Pressure	180m ³ /hr / 30mbar 105cfm / 30mbar

Technology



Datasheet download

bofainternational.com/ad-base-z

For full product features - see page 39.

OUR LEADING
TECHNOLOGY



iQ2
Intelligent (iQ2)
Operating System



iQ
Intelligent (iQ)
Operating System



DeepPleat
DeepPleat
pre filter



DeepPleat DUO
DeepPleat DUO
pre filter



HEPA
HEPA filter



ACF
Advanced carbon
filter technology

Mobile FumeKART

The FumeKART is the ideal portable air extraction and filtration unit and can be applied to a variety of applications.

Designed to filter dust particles, weld fumes, mold spores, solvent vapours and other pollutants from the work environment, the FumeKART is easy to operate and maintain and provides the additional benefit of being fully portable.

User will have flexibility and the assurance of high performance filtration. A filter condition indicator is included as a standard feature, together with three-stage filtration: pre filter, HEPA and gas filter.

Approvals CE

Dimensions	875 x 475 x 430mm 37.4 x 18.7 x 17"
Airflow/Pressure	380m ³ /hr / 100mbar 223cfm / 100mbar

Technology



Datasheet download

bofainternational.com/mobile-fumekart



For full product features - see page 39.



RFA
Reverse flow air
technology



AFC
Automatic flow
control technology



SFT
SMART filter
technology



MVS
Multi voltage
sensing unit



PATENTED
Patented
technology



SureCHECK
SureCHECK quality
standard



PROTECT
ProTECT service
plan

INLINE FILTERS

AD CYCLONE



Laser marking generates a range of particle sizes from 0.1 micron upwards so standard cyclone separators are not suitable.

BOFA's inline cyclone is designed to operate more efficiently at these lower particle sizes.

The cyclone separator has been designed specifically for use with the AD Oracle iQ and AD Oracle iQ2 (see pages 22-23) and is installed between the laser extraction point and the extractor. The airflow generated by the extraction unit powers the cyclone.

Approvals CE



Dimensions 800 x 300 x 140mm
31.5 x 11.81 x 5.51"

Datasheet download
bofainternational.com/ad-cyclone

ILF 300/600/1000



The BOFA inline pre filters have been designed specifically for applications that generate high amounts of dust or particulate.

The filter unit is positioned alongside the main BOFA fume filtration system to increase the overall filter capacity and extend the life of the main, more expensive filters.

A range of application dependent filter types and configurations are available on request.

Approvals CE

ILF 300



Dimensions 796 x 638 x 328mm
31.34 x 25.12 x 12.92"

Datasheet download
bofainternational.com/ilf-300

ILF 600



Dimensions 820 x 631 x 635mm
32.28 x 24.84 x 25"

Datasheet download
bofainternational.com/ilf-600

ILF 1000



Dimensions 650 x 617 x 763mm
25.6 x 24.3 x 30"

Datasheet download
bofainternational.com/ilf-1000



FireBOX GA/MA and FireBOX GA+/MA+ self-extinguishing inline pre filter

In the rare event that a burning ember is drawn into the fume extraction unit, there is the possibility that debris in the filters could ignite. Although any resultant fire would typically be retained within the fume extraction unit, this would cause significant damage and in extreme circumstances the risk may extend beyond the extraction unit. For processes where such risks have been identified, additional protection in the form of an inline firebox is an additional precaution. We offer two sizes of our FireBOX to cater for different size extraction units.



WHICH PRODUCT DO YOU NEED?

The FireBOX GA/GA+ is designed for general applications.

The FireBOX MA/MA+ is designed specifically for metal-based applications.

Speak to your sales representative to ensure you chose the right system.

<p>FireBOX GA/MA</p> <p>Approvals CE</p>	<p>For added safety and protection from fire. The built-in temperature controller can be set so when a 10°C temperature rise is detected, the FireBOX will activate the isolating valves and switch off the power to the extraction unit, suppressing the airflow to the FireBOX and reducing the speed of fire. If this does not suppress the fire and the temperature rises another 10°C then the fire extinguisher will be activated.</p> <p>Ideally paired with AD Oracle SA iQ; AD Oracle iQ; and AD Oracle iQ2; (page 21-23).</p>	<p>Dimensions 1186 x 480 x 600mm 46.7 x 19 x 24" (including beacon)</p> <p>Airflow Up to 380m³/hr Up to 223cfm</p> <p>Datasheet download bofainternational.com/firebox-ga bofainternational.com/firebox-ma</p>
<p>FireBOX GA+/MA+</p> <p>Approvals CE</p>	<p>For larger extraction systems. Ideally paired with AD 500 iQ; AD 1000 iQ; and AD 1500 iQ (page 24).</p>	<p>Dimensions 1380 x 615 x 900mm 54.33 x 24.21 x 35.43" (including beacon)</p> <p>Airflow Up to 1250m³/hr Up to 735cfm</p> <p>Datasheet download bofainternational.com/firebox-ga+ bofainternational.com/firebox-ma+</p>



ACCESSORIES DUST AND FUME EXTRACTION PRODUCTS

NEW



Spark Arrestor 2

BOFA's Spark Arrestor 2 unit effectively prevents potentially damaging burning particulates, generated during laser marking processes, from entering the fume extraction unit.

Hot burning particulate is transported through the specially designed plates positioned within the airflow, slowing the burning particulate down until it finally drops into the removeable drop-out chamber, so protecting the fume extractor.

Approvals CE



Dimensions

883 x 400 x 553mm
34.76 x 15.75 x 21.77"

Datasheet download

bofainternational.com/spark-arrestor-2

LASER COOLING UNITS

Our AD 200 CU is an electrically driven, cooling air unit. It supplies cool, filtered air to both the laser and power supply module. This clean, cool air ensures optimal laser performance and reliability.

The AD 350 CU is designed to supply cool, filtered air to both the laser and power supply module. This clean, cool air ensures optimal laser performance and reliability. It can also be used as a seal to increase the IP rating of the laser.

AD 200 CU

Approvals CE



Dimensions

260 x 250 x 285mm
10.2 x 9.9 x 11.2"

Datasheet download

bofainternational.com/ad-200-cu

AD 350 CU

Approvals CE



Dimensions

395 x 380 x 380mm
15.55 x 14.96 x 14.96"

Datasheet download

bofainternational.com/ad-350-cu

PIPEWORK

We offer a wide range of pipework available in 50mm, 75mm, 110mm, 125mm.

Speak to your sales representative to ensure you get the right pipework for your system.



Can't find an accessory that fits your requirements?

We have an extensive range of accessories available. On request we can create bespoke accessories to complement our full range of BOFA dust and fume extraction systems.

Speak to our experts today to find the perfect solution for your specific requirements.



BOFA International Ltd. - UK. Tel. +44 (0) 1202 699 444 Email. sales@bofa.co.uk

- Germany. Tel. +49 (0) 40 739 3735-15 Email. vertrieb@bofa.co.uk

BOFA Americas, Inc Tel. +1 (618) 205 5007 Email. sales@bofaamericas.com

Web. bofainternational.com