

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Plastic bulk

Print date: 11.01.2017

Product code: 120_bulk

Page 1 of 8

SECTION 1: Identification of the substance/mixture and of the company/undertaking**1.1. Product identifier**

Plastic bulk

1.2. Relevant identified uses of the substance or mixture and uses advised against**Uses advised against**

Reserved for industrial and professional use.

1.3. Details of the supplier of the safety data sheet

Company name:	ITW LLC & Co. KG	
Street:	Mühlackerstrasse 149	
Place:	D-75417 Mühlacker	
Telephone:	++49(0)7041-96340	Telefax: ++49(0)7041-963429
e-mail:	info@itwcp.de	
Internet:	www.itwcp.de	
Responsible Department:	Produktsicherheit	

1.4. Emergency telephone ++49(0)7041-96340
number: Mo. - Do. 8.00 - 16.30 Fr. 8.00 - 14.00

SECTION 2: Hazards identification**2.1. Classification of the substance or mixture****Regulation (EC) No. 1272/2008**

Hazard categories:

Flammable liquid: Flam. Liq. 2

Serious eye damage/eye irritation: Eye Irrit. 2A

Specific target organ toxicity - single exposure: STOT SE 3

Hazard Statements:

Highly flammable liquid and vapour.

Causes serious eye irritation.

May cause drowsiness or dizziness.

2.2. Label elements**Regulation (EC) No. 1272/2008****Hazard components for labelling**

n-butyl acetate

acetone; propan-2-one; propanone

1-methoxy-2-propanol; monopropylene glycol methyl ether

Signal word: Danger**Pictograms:****Hazard statements**

H225 Highly flammable liquid and vapour.

H319 Causes serious eye irritation.

H336 May cause drowsiness or dizziness.

Precautionary statements

P501 Dispose of contents/container to Do not empty into drains, dispose of this material and its container at hazardous or special waste collection point..

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Plastic bulk

Print date: 11.01.2017

Product code: 120_bulk

Page 2 of 8

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P261 Avoid breathing dust/fume/gas/mist/vapours/spray.
P271 Use only outdoors or in a well-ventilated area.
P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.
P403+P233 Store in a well-ventilated place. Keep container tightly closed.

Special labelling of certain mixtures

EUH066 Repeated exposure may cause skin dryness or cracking.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Hazardous components

CAS No	Chemical name			Quantity
	EC No	Index No	REACH No	
	Classification according to Regulation (EC) No. 1272/2008 [CLP]			
123-86-4	n-butyl acetate			25-50 %
	204-658-1	607-025-00-1		
	Flam. Liq. 3, STOT SE 3; H226 H336 EUH066			
107-98-2	1-Methoxy-2-propanol			20-40 %
	203-539-1		01-2119457435-35	
	Flam. Liq. 3, STOT SE 3; H226 H336			
67-64-1	acetone; propan-2-one; propanone			10-25 %
	200-662-2	606-001-00-8		
	Flam. Liq. 2, Eye Irrit. 2, STOT SE 3; H225 H319 H336 EUH066			

Full text of H and EUH statements: see section 16.

SECTION 4: First aid measures

4.1. Description of first aid measures

After inhalation

Provide fresh air. In case of accident or unwellness, seek medical advice immediately (show directions for use or safety data sheet if possible).

After contact with skin

After contact with skin, wash immediately with: Water. Change contaminated clothing. In case of skin irritation, consult a physician.

After contact with eyes

If product gets into the eye, keep eyelid open and rinse immediately with large quantities of water, for at least 5 minutes. Subsequently consult an ophthalmologist.

After ingestion

If swallowed, immediately drink: Water. Call a physician immediately. Do NOT induce vomiting.

4.2. Most important symptoms and effects, both acute and delayed

No data available

4.3. Indication of any immediate medical attention and special treatment needed

No data available

SECTION 5: Firefighting measures

5.1. Extinguishing media

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Plastic bulk

Print date: 11.01.2017

Product code: 120_bulk

Page 3 of 8

Suitable extinguishing mediaCarbon dioxide (CO₂). Foam. Extinguishing powder.**Unsuitable extinguishing media**

Water with tenside additive. Water.

5.2. Special hazards arising from the substance or mixture

Combustible. Vapours may form explosive mixtures with air. Vapours can travel considerable distances to a source of ignition where they can ignite, flash back, or explode.

5.3. Advice for firefighters

In case of fire: Wear self-contained breathing apparatus. Move undamaged containers from immediate hazard area if it can be done safely.

Additional information

Use water spray jet to protect personnel and to cool endangered containers. Suppress gases/vapours/mists with water spray jet. Contaminated fire-fighting water must be collected separately. Do not allow to enter into surface water or drains.

SECTION 6: Accidental release measures**6.1. Personal precautions, protective equipment and emergency procedures**

Remove all sources of ignition. Provide adequate ventilation. Do not breathe gas/fumes/vapour/spray. Avoid contact with skin, eyes and clothes. Wear personal protection equipment. Take precautionary measures against static discharge.

6.2. Environmental precautions

Do not allow to enter into surface water or drains. Explosion hazard. Stop and contain spill/release if it can be done safely. If this cannot be done, allow fire to burn under control.

6.3. Methods and material for containment and cleaning up

Absorb with liquid-binding material (e.g. sand, diatomaceous earth, acid- or universal binding agents). Treat the recovered material as prescribed in the section on waste disposal.

SECTION 7: Handling and storage**7.1. Precautions for safe handling****Advice on safe handling**

If handled uncovered, arrangements with local exhaust ventilation have to be used. Do not breathe gas/fumes/vapour/spray.

Advice on protection against fire and explosion

Keep away from sources of ignition. - No smoking. Take precautionary measures against static discharges.

7.2. Conditions for safe storage, including any incompatibilities**Requirements for storage rooms and vessels**

Keep container tightly closed. Keep in a cool, well-ventilated place. Keep away from sources of ignition. - No smoking. Protect against direct sunlight.

Advice on storage compatibility

Do not store together with: Material, rich in oxygen, oxidizing.

SECTION 8: Exposure controls/personal protection**8.1. Control parameters**

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Plastic bulk

Print date: 11.01.2017

Product code: 120_bulk

Page 4 of 8

Exposure limits (EH40)

CAS No	Substance	ppm	mg/m ³	fibres/ml	Category	Origin
107-98-2	1-Methoxypropan-2-ol	100	375		TWA (8 h)	WEL
		150	560		STEL (15 min)	WEL
67-64-1	Acetone	500	1210		TWA (8 h)	WEL
		1500	3620		STEL (15 min)	WEL
123-86-4	Butyl acetate	150	724		TWA (8 h)	WEL
		200	966		STEL (15 min)	WEL

8.2. Exposure controls



Appropriate engineering controls

If handled uncovered, arrangements with local exhaust ventilation have to be used. Do not breathe gas/fumes/vapour/spray.

Protective and hygiene measures

Remove contaminated, saturated clothing immediately. Protect skin by using skin protective cream. After work, wash hands and face. When using do not eat or drink.

Eye/face protection

Tightly sealed safety glasses.

Hand protection

DIN EN 374 Tested protective gloves are to be worn: Butyl rubber. For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves.

Skin protection

Protective clothing:

Respiratory protection

In case of inadequate ventilation wear respiratory protection.

Environmental exposure controls

Do not empty into drains.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state:	liquid
Colour:	colourless
Odour:	characteristic

Test method

Changes in the physical state

Initial boiling point and boiling range:	56 °C
Flash point:	18 °C
Lower explosion limits:	1,8 vol. %
Upper explosion limits:	14,3 vol. %
Ignition temperature:	270 °C

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Plastic bulk

Print date: 11.01.2017

Product code: 120_bulk

Page 5 of 8

Vapour pressure: 246 hPa
(at 20 °C)
Vapour pressure: 814 hPa
(at 50 °C)
Density: 0,88 g/cm³
Solvent content: 25,00 %

SECTION 10: Stability and reactivity

10.1. Reactivity

No data available

10.2. Chemical stability

No data available

10.3. Possibility of hazardous reactions

No data available

10.4. Conditions to avoid

Keep away from heat. Ignition hazard.

10.5. Incompatible materials

No data available

10.6. Hazardous decomposition products

No data available

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity

CAS No	Chemical name				
	Exposure route	Dose		Species	Source
67-64-1	acetone; propan-2-one; propanone				
	oral	LD50	5800 mg/kg	Rat	RTECS
	dermal	LD50	20000 mg/kg	Rabbit	IUCLID
	inhalative (4 h) vapour	LC50	76 mg/l	Rat	

Irritation and corrosivity

Irritating to eyes. Vapours may cause drowsiness and dizziness.

STOT-repeated exposure

Has degreasing effect on the skin. Frequently or prolonged contact with skin may cause dermal irritation.

Additional information on tests

The classification was carried out according to the calculation method of the Preparations Directive (1999/45/EC).

SECTION 12: Ecological information

12.1. Toxicity

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Plastic bulk

Print date: 11.01.2017

Product code: 120_bulk

Page 6 of 8

CAS No	Chemical name				
	Aquatic toxicity	Dose	[h] [d]	Species	Source
67-64-1	acetone; propan-2-one; propanone				
	Acute fish toxicity	LC50	5540 mg/l	96 h	Onchorhynchus mykiss
	Acute crustacea toxicity	EC50	6100 mg/l	48 h	Daphnia magna

12.3. Bioaccumulative potential

Partition coefficient n-octanol/water

CAS No	Chemical name	Log Pow
67-64-1	acetone; propan-2-one; propanone	-0,24

Further information

The classification was carried out according to the calculation method of the Preparations Directive (1999/45/EC).

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Advice on disposal

Dispose of waste according to applicable legislation.

Waste disposal number of waste from residues/unused products

200113 MUNICIPAL WASTES (HOUSEHOLD WASTE AND SIMILAR COMMERCIAL, INDUSTRIAL AND INSTITUTIONAL WASTES) INCLUDING SEPARATELY COLLECTED FRACTIONS; separately collected fractions (except 15 01); solvents
Classified as hazardous waste.

Waste disposal number of contaminated packaging

150104 WASTE PACKAGING; ABSORBENTS, WIPING CLOTHS, FILTER MATERIALS AND PROTECTIVE CLOTHING NOT OTHERWISE SPECIFIED; packaging (including separately collected municipal packaging waste); metallic packaging

Contaminated packaging

Water (with cleaning agent). Completely emptied packages can be recycled.

SECTION 14: Transport information

Land transport (ADR/RID)

14.1. UN number:

UN1263

14.2. UN proper shipping name:

PAINT (including paint, lacquer, enamel, stain, shellac solutions, varnish, polish, liquid filler and liquid lacquer base)

14.3. Transport hazard class(es):

3

14.4. Packing group:

II

Hazard label:

3



Classification code:

F1

Special Provisions:

163 640D 650

Limited quantity:

5 L

Transport category:

2

Hazard No:

33

Tunnel restriction code:

D/E

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Plastic bulk

Print date: 11.01.2017

Product code: 120_bulk

Page 7 of 8

Other applicable information (land transport)

E2

Inland waterways transport (ADN)

14.1. UN number: UN1263

14.2. UN proper shipping name: PAINT (including paint, lacquer, enamel, stain, shellac solutions, varnish, polish, liquid filler and liquid lacquer base)

14.3. Transport hazard class(es): 3

14.4. Packing group: II

Hazard label: 3



Classification code: F1

Special Provisions: 163 640D 650

Limited quantity: 5 L

Other applicable information (inland waterways transport)

E2

Marine transport (IMDG)

14.1. UN number: UN1263

14.2. UN proper shipping name: PAINT (including paint, lacquer, enamel, stain, shellac solutions, varnish, polish, liquid filler and liquid lacquer base)

14.3. Transport hazard class(es): 3

14.4. Packing group: II

Hazard label: 3



Special Provisions: 163

Limited quantity: 5 L

EmS: F-E, S-E

Other applicable information (marine transport)

E2

Air transport (ICAO)

14.1. UN number: UN1263

14.2. UN proper shipping name: PAINT (including paint, lacquer, enamel, stain, shellac solutions, varnish, polish, liquid filler and liquid lacquer base)

14.3. Transport hazard class(es): 3

14.4. Packing group: II

Hazard label: 3



Special Provisions: A72

Limited quantity Passenger: 1 L

IATA-packing instructions - Passenger: 353

IATA-max. quantity - Passenger: 5 L

IATA-packing instructions - Cargo: 364

**Safety Data Sheet**

according to Regulation (EC) No 1907/2006

Plastic bulk

Print date: 11.01.2017

Product code: 120_bulk

Page 8 of 8

IATA-max. quantity - Cargo:

60 L

Other applicable information (air transport)

E2

: Y341

14.5. Environmental hazards

ENVIRONMENTALLY HAZARDOUS: no

SECTION 15: Regulatory information**15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture****EU regulatory information**

2004/42/EC (VOC): 50 % (446,5 g/l)

National regulatory information

Water contaminating class (D): 1 - slightly water contaminating

SECTION 16: Other information**Relevant H and EUH statements (number and full text)**

H225	Highly flammable liquid and vapour.
H226	Flammable liquid and vapour.
H319	Causes serious eye irritation.
H336	May cause drowsiness or dizziness.
EUH066	Repeated exposure may cause skin dryness or cracking.

(The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)