

**Technical Data Sheet** 

# CRAMOLIN® MULTI Art. No. 116

## **Product description**

MULTI is a multifunctional lubricant for all electronic and mechanical equipment in workshops and in the industry. It forms a clear invisible film and is harmless to plastic, rubber and paint. Special inhibitors guarantee excellent corrosion protection and lubrication. MULTI displaces moisture, eliminates short circuits, starts wet engines and ensures long-lasting operational liability.

## Application

Electrical/Mechanical equipment: Ignition systems, lighting systems, electronic motor car equipment, carburetors, screws, locks,

seat rails, pedals, etc.

Workshop/Industry: Electrical or mechanical precision instruments, tools, metal parts, relays, switches, electronic equipment, etc.

Hobby, House, Garden, Do-it-yourself: Lawn mowers, boat engines, bicycles, motorbikes, electric appliances, arms, inline skates, sliding doors, hinges, etc.

### **Please note**

Insert the extension tube into the spray button and apply a thin film on the surface. The high penetrating capability of MULTI enables it to reach places of difficult access. Cleaning instructions of appliance producer to be taken into account. Further information concerning MULTI to be found in recent MSDS. ignition. No smoking during use.



### **Technical Data**

Color:	yellowish
Specific gravity (20° C):	0,81[g/cm3]
Odor:	characteristic, mild
Boiling range of the solvents:	180 - 210[° C]
Temperature range:	- 40 to +150 [° C]
Viscosity oil (40° C):	30-35 mm <sup>2</sup> /s
Corrosion protection:	
up to 500 h salt spray resistant	
Lubrication property:	up to 790 kg (Falex)

#### Storage / Shelf Life

Shelf life is 2 years if stored correctly. Package after emptying to be disposed via metal scrap.

ITW Chemische Produkte GmbH Co. KG Mühlacker Strasse 149, D-75417 Mühlacker Telefon +49 7041 96 34 0, Telefax +49 7041 96 34 29 e-mail info@itwcp.de, website <u>www.itwcp.de</u> January 2010